



Wire \_\_\_\_\_ Tinned copper  
 Gauge \_\_\_\_\_ AWG 28/7 0,089 mm<sup>2</sup>  
 Voltage rating \_\_\_\_\_ 300 Vr.m.s  
 Current rating \_\_\_\_\_ 2,1A at 25°C  
 Capacity unbalanced \_\_\_\_\_ 45,9 pF/m at 1 MHz  
 Impedance unbalanced \_\_\_\_\_ 105 Ω  
 Propagation delay \_\_\_\_\_ 4,9 ns/m nominal  
 Insulation material \_\_\_\_\_ PVC  
 Temperature rating \_\_\_\_\_ -20°C (operating)  
 \_\_\_\_\_ -30°C (static) to +105°C  
 Flammability rating \_\_\_\_\_ Flame retardant VW1  
 Insulation resistance \_\_\_\_\_ 100 MΩ/km  
 Approval \_\_\_\_\_ UL AWM style 2651

				Dat.	Name	 All Dim. in mm Orig. Size DIN A 4	SEK 18 flat cable 26 poles	Maßstab/ Scale	
			Detail.	20/10/05	JMDR			TB 09 18 026 700X Sub.	10:1
09 18 026 7004	100 m (328 feet)	Grey	EC01360	19/02/10	SC				
09 18 026 7001 001	30,48 m (100 feet)	Black	34400	17/09/07	PK				
09 18 026 7001	30,48 m (100 feet)	Grey	33788	24/07/06	PK				
Part number	Length per reel	Color	33246	20/10/05	JMDR	HARTING EURL F-95972 Paris			
			Mod.	Dat.	Name				