HellermannTyton

Article Number: 151-00321

Description: Adhesive Base, 1.12" x 1.12", .18" Max Tie Width, .18" Hole Dia, PA66/SR T50, White, 500/pkg



Base Data Local Order Number MB4A10H4 MB4A Type Color White (WH) Features and Benefits • For use with 18 and 30 pound cable ties to provide stability when securing bundles. · Secures with rubber based adhesive backing and/or two or four screws. · 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles. Quantity Per bag **Product Description** HellermannTyton adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles. Short Description Adhesive Base, 1.12" x 1.12", .18" Max Tie Width, .18" Hole Dia, PA66/SR T50, White, 500/pkg Product Dimensions Length L (Imperial) 1.12" Length L (Metric) 28.5mm **Fixation Method** Screw Mounting and Adhesive Width W (Imperial) 1.12" Width W (Metric) 28.5mm Cable Tie Width Max. (Imperial) 0.18" Cable Tie Width Max. (Metric) 4.6mm Height H (Imperial) 0.22" Height H (Metric) 5.6mm Mounting Hole Diameter D (Imperial) 0.18" Mounting Hole Diameter D (Metric) 4.6 mm 0.8" Mounting Hole Centers (Imperial)

151-00321

HellermannTyton

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Adhesive	Synthetic rubber with base of polyethylene foam
Flammability	UL 94 V2 (excluding adhesive)
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
ROHS Compliant	Yes
UL Recognized (US and Canada)	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number(Schedule B)	3926909987
	Material Shortcut Adhesive Flammability Operating Temperature ROHS Compliant UL Recognized (US and Canada) Package Quantity (Imperial) Package Quantity (Metric)