

111-12066



Article Number: 111-12066

Description: Heavy-Duty Cable Tie, 15.2" Long, 60lb Tensile Strength, PP, Black, 500/pkg

Base Data	Local Order Number	T120R0PPH4
	Type	T120R
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> • Polypropylene cable ties provide excellent resistance to chemicals and salts. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
	Quantity Per	bag
	Product Description	HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
	Short Description	Heavy-Duty Cable Tie, 15.2" Long, 60lb Tensile Strength, PP, Black, 500/pkg
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		267.0N
Length L (Imperial)		15.35"
Length L (Metric)		390.0mm
Fixation Method		None
Identification Plate Position		none
Releasable Closure		No
Tie Closure		plastic pawl
Variant		Inside Serrated
Width W (Imperial)		0.3"
Width W (Metric)		7.6mm
Bundle Diameter Min. (Imperial)		0.5"
Bundle Diameter Min. (Metric)		12.7mm
Bundle Diameter Max. (Imperial)		4.1"

111-12066



Product Dimensions	Bundle Diameter Max. (Metric)	105.0mm
	Thickness T (Imperial)	0.07"
	Thickness T (Metric)	1.8mm
Material and Specifications		
	Material	Polypropylene (PP)
	Material Shortcut	PP
	Flammability	UL 94 HB
	Halogenfree	Yes
	Operating Temperature	-40°F to +239°F (-40°C to +115°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	5.2kg