

156-00306

Article Number: 156-00306

Description: Omega Clip Tie, 50lbs, Clip Dia .16"-.4" Max Bun Dia. 1.38"  
PA66HS Tie, HIRHS MNT, BLK 500/pk



Base Data	Local Order Number	156-00306
	Type	T50ROC1B
	Color	Black (BK)
	Features and Benefits	Omega Clips secure cables to tubular frame rails. The cable tie is fastened to the tubular frame rail and the solar cable snaps into the clip. The cable can be removed from the clip and reinstalled without additional fasteners.
	Quantity Per	bag
	Short Description	Omega Clip Tie, 50lbs, Clip Dia .16"-.4" Max Bun Dia. 1.38" PA66HS Tie, HIRHS MNT, BLK 500/pk
Product Dimensions	Minimum Tensile Strength (Imperial)	50.0lbs
	Minimum Tensile Strength (Metric)	225N
	Length L (Imperial)	7.9"
	Length L (Metric)	202mm
	Fixation Method	Omega Clips
	Identification Plate Position	none
	Tie Closure	plastic pawl
	Width W (Imperial)	0.181"
	Width W (Metric)	4.6mm
	Height H (Imperial)	0.05"
	Height H (Metric)	1.2mm
	Bundle Diameter Min. (Imperial)	0.16"
	Bundle Diameter Min. (Metric)	4.0mm
	Bundle Diameter Max. (Imperial)	1.8"
	Bundle Diameter Max. (Metric)	45.0mm
Thickness T (Imperial)	0.05"	

156-00306



Product Dimensions	Thickness T (Metric)	1.2mm
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
	Material Shortcut	PA66HIRHS
	Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +221°F (-40°C to +105°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	2.6kg