

111-04854

HellermannTyton

Article Number: 111-04854

Description: Standard Cable Tie, 8" Long, 50lb Tensile Strength, PA66, Green, 1000/pkg



| Base Data | |
|-------------------------------------|---|
| Local Order Number | T50R5M4 |
| Type | T50R |
| Color | Green (GN) |
| Features and benefits | <ul style="list-style-type: none"> • Inside serrations allow for strong hold on cables and wire bundles. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation. |
| Quantity Per | bag |
| Product Description | HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation. |
| Short Description | Standard Cable Tie, 8" Long, 50lb Tensile Strength, PA66, Green, 1000/pkg |
| Product Dimensions | |
| Minimum Tensile Strength (Imperial) | 50.0lbs |
| Minimum Tensile Strength (Metric) | 225.0N |
| Length L (Imperial) | 8.0" |
| Length L (Metric) | 202.0mm |
| Fixation Method | None |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.18" |
| Width W (Metric) | 4.6mm |
| Bundle Diameter Min. (Imperial) | 0.06" |
| Bundle Diameter Min. (Metric) | 1.5mm |
| Bundle Diameter Max. (Imperial) | 1.97" |

111-04854



| | | |
|-----------------------------|-------------------------------|----------------------------------|
| Product Dimensions | Bundle Diameter Max. (Metric) | 50.0mm |
| | Thickness T (Metric) | 1.2mm |
| Material and Specifications | | |
| | Material | Polyamide 6.6 (PA66) |
| | Material Shortcut | PA66 |
| | US MILSPEC | MS3367-1-5 |
| | Flammability | UL 94 V2 |
| | Halogenfree | Yes |
| | Operating Temperature | -40°F to +185°F (-40°C to +85°C) |
| | ROHS Compliant | Yes |
| | Certification/Specification | SAE - AS33671 |
| | UL Listed (US and Canada) | Yes |
| | UL Recognized (US and Canada) | Yes |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 1000 |
| | Package Quantity (Metric) | 1000 |
| | Customs Number(Schedule B) | 3926909987 |