



Article Number: 151-00621

Description: Convoluted Tube Clip, Max Bun Dia .06", PA66HIRHS,

Black, 1,500/box

Base Data		
	Local Order Number	151-00621
	Туре	CTCL16FT6LG
	Color	Black (BK)
	Features and Benefits	 Extended fir tree allows for a wide range of panel thicknesses. Staggered fir tree branch design provides low insertion forces and high extraction forces. Initial fir tree serves as a locating feature for assistance in blind assembly applications.
	Quantity Per	box
	Product Description	HellermannTyton's Clamping Convoluted Tube Clip provides a more robust securing solution than traditional convoluted tube clips. Once clamped down, the internal locking feature engages to provide extra strong retention force which is important for applications where both direct vertical and side to side load forces are a concern. Also, an internal rib feature spans the diameter of the clip which provides a secure fit around the indent found on convoluted tubing.
	Short Description	Convoluted Tube Clip, Max Bun Dia .06", PA66HIRHS, Black, 1,500/box
Product Dimensions		
	Fixation Method	Fir Tree
	Width W (Imperial)	1.7"
	Width W (Metric)	43.9mm
	Height H (Imperial)	2.6"
	Height H (Metric)	65.5mm
	Bundle Diameter Max. (Imperial)	0.6"
	Bundle Diameter Max. (Metric)	16.0mm
	Panel Thickness Max. (Imperial)	0.5"
	Panel Thickness Max. (Metric)	13.0mm
	Panel Thickness Min. (Imperial)	0.02"
	Panel Thickness Min. (Metric)	0.7mm
	Mounting Hole Diameter D (Imperial)	0.25 - 0.28"

generated on: 4/28/2017

151-00621



Mounting Hole Diameter D (Metric)	6.3 - 7.0 mm
Mounting Hole Diameter D Min. (Imperial)	0.25"
Mounting Hole Diameter D Max. (Imperial)	0.275"
Nominal Diameter (Imperial)	5/8"
Nominal Diameter (Metric)	16.0mm
Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut	PA66HIRHS
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	1500
Package Quantity (Metric)	1500
Customs Number(Schedule B)	3926909987
	Mounting Hole Diameter D Min. (Imperial) Mounting Hole Diameter D Max. (Imperial) Nominal Diameter (Imperial) Nominal Diameter (Metric) Material Material Shortcut Operating Temperature ROHS Compliant Package Quantity (Imperial) Package Quantity (Metric)

generated on: 4/28/2017