



Article Number: 181-00024

Slotted Cable and Wiring Duct, 1" x 2", Non-Adhesive, PVC, Black, 120 ft/carton Description:

Base Data		
	Local Order Number	181-00024
	Туре	SL1X2
	Color	Black (BK)
	Features and Benefits	 Strong fingers prevent unwanted breaking. Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct. Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection.
	Quantity Per	carton
	Product Description	Pro-Duct slotted wall wiring duct features break-away fingers which provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a wider opening is required. The lower score line allows the sidewall to be smoothly cut for joints and "T's".
	Technical Description	Non-Adhesive
	Short Description	Slotted Cable and Wiring Duct, 1" x 2", Non-Adhesive, PVC, Black, 120 ft/carton
Product Dimensions		
	Length L (Imperial)	6.0ft
	Length L (Metric)	1.83m
	Width W (Imperial)	1.0"
	Width W (Metric)	25.4mm
	Width W2 (Imperial)	1.0"
	Width W2 (Metric)	25.4mm
	Width W3 (Imperial)	0.4"
	Width W3 (Metric)	10.2mm
	Width W4 (imperial)	1.0"
	Width W4 (metric)	25.4mm
	Width W5 (imperial)	1.62"
	Width W5 (metric)	41.1mm

generated on: 4/28/2017

181-00024



Product Dimensions Height H (Imperial) Height H (Metric) Mounting Hole Centers (Imperial) 2.07" 52.6mm 4.0"	
Height H (Metric) 52.6mm	
Mounting Hole Centers (Imperial) 4.0"	
Material and Specifications	
Material Polyvinylchloride (PVC)	
Material Shortcut PVC	
Flammability self-extinguishing	
Operating Temperature +122°F (+50°C)	
ROHS Compliant Yes	
Certification/Specification CSA	
UL Recognized (US) Yes	
Logistic and Packaging	
Package Quantity (Imperial) 120ft	
Package Quantity (Metric) 36.6m	
Customs Number(Schedule B) 3925900000	

generated on: 4/28/2017