


- Protection level: IP20  
 - Temperature range: -10° C ... +70° C

14	33012410600005	FO Multi Mode, 50/125 μm	60000 ± 600
13	33012410500005		50000 ± 500
12	33012410300005		30000 ± 300
11	33012410200005		20000 ± 200
10	33012410100005		10000 ± 100
9	33012410090005		9000 ± 90
8	33012410080005		8000 ± 80
7	33012410070005		7000 ± 70
6	33012410060005		6000 ± 60
5	33012410050005		5000 ± 50
4	33012410040005		4000 ± 40
3	33012410030005		3000 ± 30
2	33012410020005		2000 ± 20
1	33012410010005		1000 ± 15
Cont. no.	Part. no.	Type of cable	Dim. a[mm]

X (2:1)

(without protection cap)




Loading-Plan

A — red — B  
 B — green — A

Y (2:1)

(without protection cap)



	All rights reserved	Created by	Inspected by	Standardisation	Date	State
	Department EC PD - RO	OLESCHR	AVRAM	HOFFMANN	2013-07-01	Final Release
HARTING Electronics GmbH D-32339 Espelkamp		Title Fiber optic jumper cord		Doc-Key / ECM-Nr. 100210841/UGD/008/C 50000063846		Rev. C
		Type	Number		Page	
		TB	3301241XXX0005		1/1	