

156-00072

# HellermannTyton

Article Number: 156-00072

 Description: Heavy-Duty Fir Tree Mount Cable Tie, 9" x .5", .04"-.62"  
 Panel Thickness, PA66HIRHSUV, Black,100/pkg


Base Data	
Local Order Number	156-00072
Type	WSSFT9B
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"> <li>• The "H" profile provides a broad surface contact to minimize the pinching of bundles.</li> <li>• Heavy duty fir tree mounts are equipped with a friction tab that will hold the tie in the mount, allowing them to be preassembled prior to installation.</li> <li>• Designed specifically for HellermannTyton 120 - 250 lb. cable ties for heavy duty applications.</li> </ul>
Quantity Per	bag
Product Description	HellermannTyton heavy duty fir tree mounts are designed with heavy duty applications in mind. These are optimized for up to 3 to 1 extraction versus insertion force to make assembly fast and easy. These mounts are sold as an assembly with a cable tie.
Short Description	Heavy-Duty Fir Tree Mount Cable Tie, 9" x .5", .04"-.62" Panel Thickness, PA66HIRHSUV, Black,100/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	120.0lbs
Minimum Tensile Strength (Metric)	534N
Length L (Imperial)	9.0"
Length L (Metric)	228.0mm
Fixation Method	Fir Tree
Identification Plate Position	none
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.5"
Width W (Metric)	12.7mm
Width W2 (Imperial)	0.51"
Width W2 (Metric)	13.0mm
Height H (Imperial)	1.1"

156-00072



Product Dimensions	Height H (Metric)	28.5mm
	Height H2 (Imperial)	0.73"
	Height H2 (Metric)	18.4mm
	Bundle Diameter Max. (Imperial)	2.3"
	Bundle Diameter Max. (Metric)	57.0mm
	Disc Diameter (Imperial)	0.9"
	Disc Diameter (Metric)	21.6mm
	Panel Thickness Max. (Imperial)	0.62"
	Panel Thickness Max. (Metric)	15.8mm
	Panel Thickness Min. (Imperial)	0.04"
	Panel Thickness Min. (Metric)	1.0mm
	Mounting Hole Diameter D (Metric)	8.75 - 9.25 mm
	Mounting Hole Diameter D Min. (Imperial)	0.34"
	Mounting Hole Diameter D Max. (Imperial)	0.36"
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
	Material Shortcut	PA66HIRHSUV
	Flammability	UL 94 HB
	Operating Temperature	-65°F to +212°F (-54°C to +100°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	100
	Package Quantity (Metric)	100
	Customs Number(Schedule B)	3926909987