



Article Number: 170-03109

Description: Plenum Rated Expandable Braided Sleeving (Halar), 1.0"

Dia, White, 65 ft/reel

Base Data		
	Local Order Number	170-03109
	Туре	BSHLR1010
	Color	White (WH)
	Features and Benefits	 Meets UL 2024 and NFPA 262 specifications meets requirements for use in plenum applications. Technically advanced monofilament material is rated as low smoke, flame resistant and can withstand exposure to Cobal 60 radiation. Exceeds requirements of FMVSS 302 as well as aviation industry requirements of FAR25.
	Quantity Per	reel
	Product Description	Halar self-extinguishing sleeving is used where flammability, high temperature endurance and low outgassing are the primary concern.
	Short Description	Plenum Rated Expandable Braided Sleeving (Halar), 1.0" Dia, White, 65 ft/reel
Product Dimensions		
	Length L (Imperial)	65.0ft
	Length L (Metric)	19.8m
	Reel Length (imperial)	65.0ft
	Bundle Diameter Min. (Imperial)	0.63"
	Bundle Diameter Min. (Metric)	16.0mm
	Bundle Diameter Max. (Imperial)	1.63"
	Bundle Diameter Max. (Metric)	41.3mm
	Diameter D (imperial)	1.0"
	Nominal Diameter (Imperial)	1"
	Nominal Diameter (Metric)	25.4mm
Material and Specifications		
	Material	Polyamide 6.6 (PA66E/CTFE)
	Material Shortcut	PA66E/CTFE

generated on: 4/28/2017

170-03109



Material and Specifications	Flammability	UL VW-1
	Operating Temperature	-103°F to +302°F (-75°C to +150°C)
	ROHS Compliant	Yes
	Certification/Specification	UL2024
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	65ft
	Package Quantity (Metric)	19.8m
	Customs Number(Schedule B)	3926909987
	Weight (imperial)	1.43lbs
	Weight (Metric)	0.65kg

generated on: 4/28/2017