HellermannTyton

Article Number: 596-82822

Description:

Thermal Transfer Labels, 1.5" x .25", 2 Across, Polyester, White, 10,000/roll

HellermannTyton

| Base Data | | |
|-----------------------|---------------------------------|--|
| | | |
| | Local Order Number | TAG82T2-822 |
| | Туре | TAG82T2 |
| | Color | White (WH) |
| | Features and benefits | Thermal transfer labels are made with high performance materials for long term industrial applications. Labels can be printed in any standard thermal transfer printer giving the user options for printing and eliminating the need to be dedicated to one printer model. The labels are available in a wide variety of sizes so that finding a label for a particular application is easy. |
| | Quantity Per | reel |
| | Product Description | Labels are made with various high performance materials including polyester, metalized polyester, clear polyester, cloth, polyimide and the Durattach label stock. The construction includes an aggressive acrylic adhesive and abrasion and chemical resistant top coatings that are made to accept ink from a thermal transfer printer. The product is supplied on rolls on a 3" cardboard core. |
| | Short Description | Thermal Transfer Labels, 1.5" x .25", 2 Across, Polyester, White, 10,000/roll |
| Product Dimensions | | |
| | Width W (Imperial) | 1.50" |
| | Width W (Metric) | 38.1mm |
| | Height H (Imperial) | 0.25" |
| | Height H (Metric) | 6.35mm |
| | Horizontal Repeat HR (imperial) | 1.50" |
| | Horizontal Repeat HR (metric) | 38.1mm |
| | Print Method | Thermal transfer |
| | Vertical Repeat VR (metric) | 7.62mm |
| | Vertical Repeat VR (imperial) | 0.30" |
| | Width of Liner WL (metric) | 81.28mm |
| | Width of Liner WL (imperial) | 3.20" |

596-82822

HellermannTyton

| Material and Specifications | | |
|-----------------------------|--------------------------------|-----------------------------------|
| | Material | Type 822, Polyester, white (WH) |
| | Material Shortcut | 822 |
| | Adhesive | Acrylic |
| | Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
| | Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
| | ROHS Compliant | Yes |
| | Certification/Specification | UL-Recognized |
| | UL Recognized (US and Canada) | Yes |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 10000 |
| | Package Quantity (Metric) | 10000 |
| | Customs Number(Schedule B) | 3919102055 |
| | Labels per Row | 2 |