

20 19 18 17 16 15 14 13 12 11 9 8 7 6 5 4 3 2 1

VIEW ON MATING SIDE

○	C	C	C	C	C	C	C	C	C	C	X	C	C	C	C
△	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
○	D	A	A	A	A	A	Z	A	A	A	A	A	A	A	Z

16 15 14 13 12 = 11 10 9 8 7 6 5 4 3 2 -

A = 13 STANDARD CONTACTS L = 3  
 B = 16 STANDARD CONTACTS L = 3  
 C = 15 STANDARD CONTACTS L = 3  
 D = 1 LMFB CONTACTS -0.6 L = 3  
 Z = 2 FMLB CONTACTS +0.6 L = 3  
 X = 1 FMLB CONTACTS +0.6 L = 3  
 S = 48 TOTAL NUMBER OF CONTACTS

MARKING	STANDARD
PERFORMANCE LEVEL	G2/0 = CONTACT AREA LEVEL2 / TERMINATION TIN
FLUX PROOF	NO
FIXING CLIP	NO
DIMENSIONS	SD-85003-0002 SHT 1

X	G2/0	c5
Z	G2/0	a1,9
D	G2/0	a16
C	G2/0	c1-4,6-16
B	G2/0	b1-16
A	G2/0	a2-8,10-15
CONTACT SYMBOL	PERFORMANCE LEVEL	CONTACT POSITION NUMBER

EC NO. I 2004-XXXX DRAWN: S. 09/09/03 CHK: G.L. 09/09/03 APPR: L. 09/09/03	QUALITY SYMBOLS	GENERAL TOLERANCES: (UNLESS SPECIFIED)	SCALE	DESIGN UNITS	DIMENSIONS:		SHT	REV
	MAJOR			<input checked="" type="checkbox"/> MM <input type="checkbox"/> INCH	<input type="checkbox"/> MM <input type="checkbox"/> INCH	<input checked="" type="checkbox"/> MM ONLY		REVISE ON CAD ONLY
	CRITICAL							
REV	DESCRIPTION							
B								

24-border.DGN REV A 96/06/12 LEVEL 6 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1