



Article Number: 211-00135

Description: P Clamp, .375" Width, .25" Max Bundle Dia, .203"

Mounting Hole Dia, PA66, White, 1000/pkg

| Base Data                      |                                     |   |
|--------------------------------|-------------------------------------|---|
|                                | Local Order Number                  | T3D03120M4  |
|                                | Туре                                | T3D0250   |
|                                | Color                               | White (WH)  |
|                                | Features and Benefits               | <ul> <li>P-Clamps easily guide and locate wire and cables up to 0.625" in diameter.</li> <li>Designed with a radiused edge to prevent chaffing and cutting into insulation.</li> </ul>                      |
|                                | Quantity Per                        | bag   |
|                                | Product Description                 | HellermannTyton P Clamps easily guide and locate wires and cables. The clamps are designed with a radiused edge to prevent chaffing and cutting into insulation. Available sizes up to 1" bundle diameters. |
|                                | Short Description                   | P Clamp, .375" Width, .25" Max Bundle Dia, .203" Mounting Hole Dia, PA66, White, 1000/pkg   |
| Product<br>Dimensions          |                                     |   |
|                                | Fixation Method                     | screw-hole  |
|                                | Variant                             | Closed  |
|                                | Width W (Imperial)                  | 0.375"  |
|                                | Width W (Metric)                    | 9.53mm  |
|                                | Bundle Diameter Max. (Imperial)     | 0.25"   |
|                                | Bundle Diameter Max. (Metric)       | 6.35mm  |
|                                | Mounting Hole Diameter D (Imperial) | 0.203"  |
|                                | Mounting Hole Diameter D (Metric)   | 5.1 mm  |
|                                | Wall Thickness WT (Imperial)        | .050"   |
|                                | Wall Thickness WT (Metric)          | 1.3mm   |
|                                | Mounting Hole Centers (Imperial)    | 0.41"   |
| Material and<br>Specifications |                                     |   |
|                                | Material                            | Polyamide 6.6 (PA66)  |
|                                | Material Shortcut                   | PA66  |

generated on: 4/28/2017

## 211-00135



| Material and<br>Specifications | Flammability                  | UL 94 V2                         |
|--------------------------------|-------------------------------|----------------------------------|
|                                | Operating Temperature         | -40°F to +185°F (-40°C to +85°C) |
|                                | ROHS Compliant                | Yes                              |
|                                | UL Recognized (US and Canada) | Yes                              |
| Logistic and Packaging         |                               |                                  |
|                                | Package Quantity (Imperial)   | 1000                             |
|                                | Package Quantity (Metric)     | 1000Pieces                       |
|                                | Customs Number(Schedule B)    | 3926909987                       |

generated on: 4/28/2017