
## **HellermannTyton**



Article Number: 170-03108

Plenum Rated Expandable Braided Sleeving (Halar), 1.0" Dia, Black, 65 ft/reel

Base Data		
	Local Order Number	170-03108
	Туре	BSHLR100
	Color	Black (BK)
	Features and Benefits	<ul> <li>Meets UL 2024 and NFPA 262 specifications meets requirements for use in plenum applications.</li> <li>Technically advanced monofilament material is rated as low smoke, flame resistan and can withstand exposure to Cobal 60 radiation.</li> <li>Exceeds requirements of FMVSS 302 as well as aviation industry requirements of FAR25.</li> </ul>
	Quantity Per	reel
	Product Description	Halar self-extinguishing sleeving is used where flammability, high temperature endurance and low outgassing are the primary concern.
	Short Description	Plenum Rated Expandable Braided Sleeving (Halar), 1.0" Dia, Black, 65 ft/reel
Product Dimensions		
	Length L (Imperial)	65.0ft
	Length L (Metric)	19.8m
	Reel Length (imperial)	65.0ft
	Bundle Diameter Min. (Imperial)	0.63"
	Bundle Diameter Min. (Metric)	15.9mm
	Bundle Diameter Max. (Imperial)	1.63"
	Bundle Diameter Max. (Metric)	41.3mm
	Diameter D (imperial)	1.0"
	Nominal Diameter (Imperial)	1"
	Nominal Diameter (Metric)	25.4mm
Material and Specifications		
	Material	Polyamide 6.6 (PA66E/CTFE)
	Material Shortcut	PA66E/CTFE

## 170-03108

## HellermannTyton

Material and Specifications	Flammability	UL VW-1
	Operating Temperature	-103°F to +302°F (-75°C to +150°C)
	ROHS Compliant	Yes
	Certification/Specification	UL2024
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	65ft
	Package Quantity (Metric)	19.8m
	Customs Number(Schedule B)	3926909987
	Weight (imperial)	1.43lbs
	Weight (Metric)	0.65kg