


Extended length is with 500g of force



P1	COLOR
1	WHITE
2	ORANGE
3	BLACK
4	RED
5	GREEN
6	YELLOW
7	BLUE
8	BROWN

Material:

- Plug Housing : Polycarbonate, clear
- Plug Terminal: 0.36" [0.14MM] Thick Phosphor Bronze
- Connector: 50" of Selective Gold Contact Plating
 - Area, Gold flash over the remainder
 - Over 2.54µ[.000100] thick nickel underplate
- Conductor(X4C): 26AWG (0.12X12) Bare Copper
- Insulation(X43): PP6331 ID 0.95-1.0
- Jacket: PVC NOUL 80P
- Package: Individual PE Bag



Extended Length ("L2")	Typical Retracted Length ("L1")
168.0 Inches - 193.2 Inches	75.0 Inches
4,267.2MM-4,907.28MM	1,905.0MM

Electrical:

- Voltage rating: 30V (DC)



Scale	1:1	Name	Chappell
TOLERANCE		Drawn	11.21.11
X.X	±0.40	Approved	
X.XX	±0.25		
X.XXX	±0.15		
Angle	±3°		
Modification		Date	Name



Item No.	AT-C-26-8/8/W-14-OE
Title	NON-UL 26AWG (0.16/7)*8C, O.D.: 2.4*8.8MM, Single Plug, 50µ" of contact plating, White
Drawing No.	
Replace	Sheet

rev00