

854-44352

HellermannTyton

Article Number: 854-44352

Description: Grip Tie, UL94V0-2 Flame Rated, .5" x 6.0", PA6/PP, Maroon, 10/pkg



Base Data	
Local Order Number	GT.50X6MP2V2
Type	GT.50X6
Color	Maroon (MN)
Features and Benefits	<ul style="list-style-type: none"> • UL94V0-2 flame rate material allow use in air handling spaces. • Features quick release for repetitive access to cable and wire. • Can be opened and closed numerous times without failure. • Adjustable so one size can accommodate multiple bundle sizes.
Quantity Per	bag
Product Description	The Grip Tie is a low profile, one piece fastening device. Constructed of a hook and loop design, laminated back to back, the Grip Tie features quick release for repetitive access to cable and wire. Grip Ties are available in a variety of colors and are versatile enough for applications ranging from network installations to bundling power cords.
Short Description	Grip Tie, UL94V0-2 Flame Rated, .5" x 6.0", PA6/PP, Maroon, 10/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	40.0lbs
Minimum Tensile Strength (Metric)	177.93N
Length L (Imperial)	6.0"
Length L (Metric)	152.4mm
Length L2 (Imperial)	1.5"
Length L2 (Metric)	38.1mm
Width W (Imperial)	0.5"
Width W (Metric)	12.7mm
Width W2 (Imperial)	1.0"
Width W2 (Metric)	25.4mm
Bundle Diameter Max. (Imperial)	1.0"
Bundle Diameter Max. (Metric)	25.4mm

854-44352



Material and Specifications		
	Material	Polyamide 6 (PA6)
	Material Shortcut	PA
Logistic and Packaging		
	Package Quantity (Imperial)	10
	Package Quantity (Metric)	10
	Customs Number(Schedule B)	9606100000