
UNCONTROLLED DOCUMENT

CAUTION: STATIC SENSITIVE DEVICE FOLLOW PROPER E.S.D. HANDLING PROCEDURES WHEN WORKING WITH THIS PART.

Α

PART NUMBER					
SSP-CS83912					
REV.	E.C.N. NUMBER AND REVISION COMMENTS	D،	ATE		
A	E.C.N. #E11064	12.	3.03		




ELECTRO-OPTICAL CH	ARACTERISTICS TA=25°C		$V_f = 12V$			
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND	
PEAK WAVELENGTH				nm	_	
FORWARD VOLTAGE		12.0	14.0	Vf		
REVERSE VOLTAGE	5.0			V_{r}	Ir=100µA	
AXIAL INTENSITY *		500		mcd	$V_f = 12V$	
VIEWING ANGLE		50		2x theta		
EMITTED COLOR:	WHITE					
EPOXY LENS FINISH:	WATER CLEAR	LENS				

^{*} PER LED

LIMITS OF SAFE OPERATION AT 25°C PER DIE

MAX	UNITS
14	V
70	mA
1200	mW
- 1.2	mW/°C
- 40 TO +85	•C
	14 70 1200 – 1.2



NOTES:

1. FOUR LEDS PER STRIP.

UNCONTROLLED DOCUMENT *UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.020), LEAD LENGTH=±0.75 (±0.030). MIN= +DECIMAL PRECISION MAX.= +0.00 -DECIMAL PRECISION MAX.= +0.00

REV. PART NUMBER SSP-CS83912

MODULAR STRIP LIGHT, ULTRA WHITE LEDS.

CONFIDENTIAL INFORMATION THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF SUNBRITE LEDS. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY SUNBRITE LEDS, THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



286 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 FAX: +1.847.359.2867 WEB: www.sunbriteleds.com

DRAWN: CHECKED:

APPROVED: DATE: 8.1.02 PAGE: 1 OF 1