
## **HellermannTyton**



Article Number: 170-03139

Braided Sleeving, Split Wrap, 2" Dia, PET, Black, 150 ft/bulk reel

Base Data		
	Local Order Number	170-03139
	Туре	BSPSW200LB
	Color	Black (BK)
	Features and Benefits	<ul> <li>Split wrap design installs quickly, saving assembly time and future accessibility without disassembly.</li> <li>Unique construction retains shape and rigidity throughout unrolling.</li> <li>Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.</li> </ul>
	Quantity Per	box
	Product Description	A lateral split, semi-rigid and flame retardant braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.
	Short Description	Braided Sleeving, Split Wrap, 2" Dia, PET, Black, 150 ft/bulk reel
Product Dimensions		
	Length L (Imperial)	150.0ft
	Length L (Metric)	45.72m
	Reel Length (imperial)	150.0ft
	Bundle Diameter Max. (Imperial)	2.0"
	Bundle Diameter Max. (Metric)	50.8mm
	Diameter D (imperial)	2.0"
	Nominal Diameter (Imperial)	2"
	Nominal Diameter (Metric)	50.8mm
Material and Specifications		
	Material	Polyester (PET)
	Material Shortcut	PET
	Flammability	UL 94 V0

## 170-03139

## **HellermannTyton**

Material and Specifications	Operating Temperature	-94°F to +248°F (-70°C to +125°C)
	ROHS Compliant	Yes
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	150ft
	Package Quantity (Metric)	45.72m
	Customs Number(Schedule B)	3926909987
	Weight (imperial)	5.4lbs
	Weight (Metric)	2.4kg