## **HellermannTyton**

Article Number: 170-03097



Braided Sleeving, Aluminum Laminated Fiberglass, 2.5" Dia, AL/GF, Silver, 50 ft/reel

Base Data		
	Local Order Number	170-03097
	Туре	BSHTTST212SR
	Color	Silver (SR)
	Features and Benefits	<ul> <li>A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.</li> <li>Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.</li> <li>Cuts with ordinary scissors for fast, easy application.</li> </ul>
	Quantity Per	reel
	Product Description	A tubular shaped sleeving product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to deflect radiant heat away from sensitive components inside the tube.
	Short Description	Braided Sleeving, Aluminum Laminated Fiberglass, 2.5" Dia, AL/GF, Silver, 50 ft/reel
Product Dimensions		
	Length L (Imperial)	50.0ft
	Length L (Metric)	15.2m
	Reel Length (imperial)	50.0ft
	Bundle Diameter Max. (Imperial)	2.375"
	Bundle Diameter Max. (Metric)	60.3mm
	Nominal Diameter (Imperial)	2-1/2"
	Nominal Diameter (Metric)	63.5mm
Material and Specifications		
	Material	Aluminum (AL)
	Material Shortcut	AL
	Flammability	non flammable
	Operating Temperature	-76°F to +491°F (-60°C to +255°C)
	ROHS Compliant	Yes

## 170-03097

## **HellermannTyton**

Logistic and Packaging			
	Package Quantity (Imperial)	50ft	
	Package Quantity (Metric)	15.24m	
	Customs Number(Schedule B)	7019901000	
	Weight (imperial)	5.05lbs	
	Weight (Metric)	2.3kg	