

111-04897

Article Number: 111-04897

Description: High-Temp. Cable Tie, 8" Long, 40 lb Tensile Strength, PAHL, Red, 1000/pkg



Base Data	Local Order Number	T50R2HALM4
	Type	T50R
	Color	Red (RD)
	Features and Benefits	<ul style="list-style-type: none"> <li>• Halar cable ties provide excellent resistance to chemicals, radiation, high temperatures and UV exposure.</li> <li>• Inside serrations allow for strong hold on cables and wire bundles.</li> <li>• Head design provides high tensile strength with very low insertion force.</li> <li>• Bent tail ensures a quick and simple installation.</li> </ul>
	Quantity Per	bag
	Product Description	HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
	Short Description	High-Temp. Cable Tie, 8" Long, 40 lb Tensile Strength, PAHL, Red, 1000/pkg
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		180.0N
Length L (Imperial)		8.0"
Length L (Metric)		203.2mm
Fixation Method		None
Identification Plate Position		none
Releasable Closure		No
Tie Closure		plastic pawl
Variant		Inside Serrated
Width W (Imperial)		0.2"
Width W (Metric)		5.0mm
Bundle Diameter Min. (Imperial)		0.5"
Bundle Diameter Min. (Metric)		12.7mm

111-04897

**HellermannTyton**

Product Dimensions	Bundle Diameter Max. (Imperial)	1.75"
	Bundle Diameter Max. (Metric)	44.5mm
	Thickness T (Metric)	1.2mm
Material and Specifications		
	Material	Polyamide 6.6 (PA66E/CTFE)
	Material Shortcut	PA66E/CTFE
	Flammability	UL 94 V0
	Operating Temperature	-103°F to +302°F (-75°C to +150°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	1000
	Package Quantity (Metric)	1000
	Customs Number(Schedule B)	3926909987