

111-12206



Article Number: 111-12206

Description: Heavy-Duty Cable Tie, 11.8" Long, 120lb Tensile Strength, PA66, Black, 500/pkg

| Base Data | |
|-------------------------------------|---|
| Local Order Number | T120I0H4 |
| Type | T120I |
| Color | Black (BK) |
| Features and Benefits | <ul style="list-style-type: none"> • Heavy duty design to offer higher tensile strength. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation. |
| Quantity Per | bag |
| Product Description | HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation. |
| Short Description | Heavy-Duty Cable Tie, 11.8" Long, 120lb Tensile Strength, PA66, Black, 500/pkg |
| Product Dimensions | |
| Minimum Tensile Strength (Imperial) | 120.0lbs |
| Minimum Tensile Strength (Metric) | 535.0N |
| Length L (Imperial) | 11.8" |
| Length L (Metric) | 300.0mm |
| Fixation Method | None |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.3" |
| Width W (Metric) | 7.6mm |
| Cable Tie Width Max. (Imperial) | 0.3" |
| Cable Tie Width Max. (Metric) | 7.61mm |
| Bundle Diameter Min. (Imperial) | 0.2" |

111-12206



| | | |
|-----------------------------|----------------------------------|----------------------------------|
| Product Dimensions | Bundle Diameter Min. (Metric) | 5.0mm |
| | Bundle Diameter Max. (Imperial) | 3.2" |
| | Bundle Diameter Max. (Metric) | 80.0mm |
| | Cable Tie Head Length (Imperial) | 0.393" |
| | Cable Tie Head Width (Imperial) | 0.502" |
| | Thickness T (Metric) | 1.6mm |
| Material and Specifications | | |
| | Material | Polyamide 6.6 (PA66) |
| | Material Shortcut | PA66 |
| | Flammability | UL 94 V2 |
| | Halogenfree | Yes |
| | Operating Temperature | -40°F to +185°F (-40°C to +85°C) |
| | ROHS Compliant | Yes |
| Certification/Specification | UL ANSI/UL 62275 | |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 500 |
| | Package Quantity (Metric) | 500 |
| | Customs Number(Schedule B) | 3926909987 |