

111-94088

Article Number: 111-94088

Description: Stainless Steel Tie, 7.9" Long, 450lb Tensile Strength, SS304, Metal, 50/pkg



Base Data	Local Order Number	MBT8H-S
	Type	MBT8HS
	Color	Metal (ML)
	Features and Benefits	<ul style="list-style-type: none"> • 304 grade stainless steel offers excellent resistance to corrosion, weather and chemical resistance. • Ball bearing locking mechanism assures high tensile strength and easy insertion.
	Quantity Per	bag
	Product Description	HellermannTyton's stainless steel ties are designed with a ball bearing locking mechanism to assure high tensile strength and easy insertion when securing hoses, cables, pipes and more. Available in 304 or 316 grades of stainless steel, providing protection when used in corrosive environments, fire resistance and temperature extremes.
	Short Description	Stainless Steel Tie, 7.9" Long, 450lb Tensile Strength, SS304, Metal, 50/pkg
Product Dimensions	Minimum Tensile Strength (Imperial)	450.0lbs
	Minimum Tensile Strength (Metric)	2000.0N
	Length L (Imperial)	7.9"
	Length L (Metric)	201.0mm
	Fixation Method	None
	Identification Plate Position	none
	Releasable Closure	No
	Tie Closure	ball bearing lock
	Variant	No Serration
	Width W (Imperial)	0.31"
	Width W (Metric)	7.9mm
	Bundle Diameter Min. (Imperial)	0.67"
	Bundle Diameter Min. (Metric)	17.0mm
	Bundle Diameter Max. (Imperial)	2.0"

111-94088



Product Dimensions	Bundle Diameter Max. (Metric)	50.0mm
	Thickness T (Imperial)	0.01"
	Thickness T (Metric)	0.3mm
Material and Specifications		
	Material	Stainless Steel (SS304)
	Material Shortcut	SS304
	Flammability	non-burning
	Halogenfree	Yes
	Minimum Application Temperature	-
	Operating Temperature	-112°F to +1000°F (-80°C to +538°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	50
	Package Quantity (Metric)	50Pieces
	Customs Number(Schedule B)	7326908595
	Content Unit (BMEcat)	pieces
	Weight (Metric)	4.76kg