

155-05800

Article Number: 155-05800



Description: Fir Tree with Tie, 6.0" Long, Mounting Hole Diameter .26"-.28", PA66HIRHS, Black, 1,500/pkg

Base Data	Local Order Number	155-05800
	Type	T50SOSFT6E
	Color	Black (BK)
	Features and benefits	<ul style="list-style-type: none"> <li>• Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.</li> <li>• Initial fir tree serves as a locating feature for assistance in blind assembly applications.</li> <li>• Disc feature provides anti-rattle protection in high vibration applications.</li> </ul>
	Quantity Per	bag
	Product Description	Fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. The mount provides low insertion and high extraction force.
	Short Description	Fir Tree with Tie, 6.0" Long, Mounting Hole Diameter .26"-.28", PA66HIRHS, Black, 1,500/pkg
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		150N
Length L (Imperial)		6.0"
Length L (Metric)		160mm
Fixation Method		Fir Tree
Identification Plate Position		none
Releasable Closure		No
Tie Closure		plastic pawl
Variant		Outside Serrated
Width W (Imperial)		0.19"
Width W (Metric)		4.6mm
Height H (Imperial)		0.33"
Bundle Diameter Min. (Imperial)		0.04"
Bundle Diameter Min. (Metric)		1.6mm

155-05800



Product Dimensions	Bundle Diameter Max. (Imperial)	1.4"
	Bundle Diameter Max. (Metric)	35.0mm
	Disc Diameter (Imperial)	0.63"
	Disc Diameter (Metric)	16.0mm
	Panel Thickness Max. (Imperial)	0.12"
	Panel Thickness Max. (Metric)	3.0mm
	Panel Thickness Min. (Imperial)	0.03"
	Panel Thickness Min. (Metric)	0.75mm
	Mounting Hole Diameter D (Imperial)	0.26 - 0.28"
	Mounting Hole Diameter D (Metric)	6.5 - 7.0 mm
	Mounting Hole Diameter D Min. (Imperial)	0.26"
	Mounting Hole Diameter D Max. (Imperial)	0.28"
	Thickness T (Imperial)	0.05"
	Thickness T (Metric)	1.35mm
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
	Material Shortcut	PA66HIRHS
	Operating Temperature	-40°F to +221°F (-40°C to +105°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	1500
	Package Quantity (Metric)	1500Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	2.0kg