

# Gecko Screw-Lok Connectors

## Male Crimp Contacts – Pre-Crimped Wires

- Ready for assembling to housing.
- Crimp barrel meets all crimp guidelines and standards.
- 2A current capacity, resists high vibration and shock.
- Withstands extremes of temperature: -65°C to +150°C.
- For non-standard cable lengths, please contact [cables@harwin.com](mailto:cables@harwin.com) with your requirements.



<b>MALE SINGLE ENDED</b>	<b>MALE – MALE</b>
<b>MALE – FEMALE</b>	<b>TOOLS</b>
	<p><b>Contact Insertion/Removal Tool</b> – Z125-902</p> <ul style="list-style-type: none"> <li>➤ Male crimp housing and loose contacts shown on previous pages.</li> <li>➤ Instruction sheets available at <a href="http://www.harwin.com/instructions">www.harwin.com/instructions</a>.</li> </ul>

### HOW TO ORDER

**G125 – M WX XXXX X 94**

**SERIES CODE**

CABLE COLOUR	
94	White

GENDER – FIRST END	
M	Male

TERMINATION – SECOND END	
L	Loose cut end
F	Female
M	Male

CABLE SIZE	
W1	26 AWG
W2	28 AWG
W3	30 AWG
W4	32 AWG

CABLE LENGTH	
0150	150mm
0300	300mm (double-ended)
0450	450mm (single-ended)

All dimensions in mm.

Patent Published