

Article Number: 184-15202



Slotted Cable and Wiring Duct, High-Density, 1.5" x 2", Non-Adhesive, PVC, Gray, 120 ft/carton Description:

Base Data		
	Local Order Number	184-15202
	Type	SLHD1.5X2
	Color	Gray (GY)
	Features and Benefits	Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a
	r eatures and benefits	neater appearance. • Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation. • Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to accommodate compact designs and ease installation.
	Quantity Per	carton
	Product Description	Pro-Duct high density, slotted wiring duct features narrow fingers, a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.
	Technical Description	Non-Adhesive
	Short Description	Slotted Cable and Wiring Duct, High-Density, 1.5" x 2", Non-Adhesive, PVC, Gray, 120 ft/carton
Product Dimensions		
	Length L (Imperial)	6.0ft
	Length L (Metric)	1.83m
	Width W (Imperial)	1.5"
	Width W (Metric)	38.1mm
	Width W2 (Imperial)	1.5"
	Width W2 (Metric)	38.1mm
	Width W3 (Imperial)	0.16"
	Width W3 (Metric)	4.1mm
	Width W4 (imperial)	0.4"
	Width W4 (metric)	10.2mm
	Width W5 (imperial)	1.60"
	Width W5 (metric)	40.6mm

4/28/2017 generated on:

184-15202



Dimensions Height H (Metric) Mounting Hole Centers (Imperial) Material and Specifications Material Shortcut Flammability Operating Temperature ROHS Compliant Certification/Specification UL Recognized (US) 52.6mm 52.6mm Polyvinylchloride (PVC) Polyvinylchloride (PVC) PVC Flammability Self-extinguishing +122°F (+50°C) ROHS Compliant Yes Logistic and			
Height H (Metric) 52.6mm Mounting Hole Centers (Imperial) 2.0" Material and Specifications Material Polyvinylchloride (PVC) Material Shortcut PVC Flammability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification UL UL Recognized (US) Yes Logistic and Packaging Package Quantity (Imperial) 120ft Package Quantity (Imperial) 36.6m	Product Dimensions	Height H (Imperial)	2.07"
Material and Specifications Material Material Material Polyvinylchloride (PVC) Material Shortcut PVC Flammability Self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification UL UL Recognized (US) Yes Logistic and Packaging Package Quantity (Imperial) Package Quantity (Metric) 120ft Package Quantity (Metric)		Height H (Metric)	52.6mm
Specifications Material Material Shortcut Flammability Operating Temperature ROHS Compliant Certification/Specification UL UL Recognized (US) Package Quantity (Imperial) Package Quantity (Metric) Package Quantity (Metric) Package Quantity (Metric) Polyvinylchloride (PVC) PVC Flammability self-extinguishing +122°F (+50°C) UL UL Package Quantity (Imperial) 120ft Package Quantity (Metric) 36.6m		Mounting Hole Centers (Imperial)	2.0"
Material Shortcut PVC Flammability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification UL UL Recognized (US) Yes Logistic and Packaging Package Quantity (Imperial) 120ft Package Quantity (Metric) 36.6m	Material and Specifications		
Flammability Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification UL UL Recognized (US) Yes Logistic and Packaging Package Quantity (Imperial) Package Quantity (Metric) 120ft Package Quantity (Metric) 36.6m		Material	Polyvinylchloride (PVC)
Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification UL UL Recognized (US) Yes Logistic and Packaging Package Quantity (Imperial) 120ft Package Quantity (Metric) 36.6m		Material Shortcut	PVC
ROHS Compliant Certification/Specification UL UL Recognized (US) Yes Logistic and Packaging Package Quantity (Imperial) Package Quantity (Metric) 36.6m		Flammability	self-extinguishing
Certification/Specification UL UL Recognized (US) Yes Logistic and Packaging Package Quantity (Imperial) Package Quantity (Metric) 120ft Package Quantity (Metric)		Operating Temperature	+122°F (+50°C)
Logistic and Packaging Package Quantity (Imperial) Package Quantity (Metric) 120ft Package Quantity (Metric)		ROHS Compliant	Yes
Logistic and Packaging Package Quantity (Imperial) Package Quantity (Metric) 120ft Package Quantity (Metric) 36.6m		Certification/Specification	UL
Packaging Package Quantity (Imperial) Package Quantity (Metric) 120ft Package Quantity (Metric) 36.6m		UL Recognized (US)	Yes
Package Quantity (Metric) 36.6m	Logistic and Packaging		
		Package Quantity (Imperial)	120ft
Customs Number(Schedule B) 3925900000		Package Quantity (Metric)	36.6m
		Customs Number(Schedule B)	3925900000

generated on: 4/28/2017