



Article Number: 170-03142

Description: Braided Sleeving, Split Wrap, Flame Retardant, .5" Dia,

Black, 150 ft/bulk reel

Local Order Number	170-03142
Туре	BSSWFR120B
Color	Black (BK)
Features and Benefits	 Split wrap design installs quickly, saving assembly time and future accessibility without disassembly. Unique construction retains shape and rigidity throughout unrolling. Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.
Quantity Per	reel
Product Description	A lateral split, semi-rigid and flame retardant braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.
Short Description	Braided Sleeving, Split Wrap, Flame Retardant, .5" Dia, Black, 150 ft/bulk reel
Length L (Imperial)	150.0ft
Length L (Metric)	45.7m
Reel Length (imperial)	150.0ft
Bundle Diameter Min. (Imperial)	0.5"
Bundle Diameter Min. (Metric)	12.7mm
Bundle Diameter Max. (Imperial)	0.02"
Bundle Diameter Max. (Metric)	0.5mm
Nominal Diameter (Imperial)	1/2"
Nominal Diameter (Metric)	12.7mm
Material	Polyester (PET)
	Type Color Features and Benefits Quantity Per Product Description Short Description Length L (Imperial) Length L (Metric) Reel Length (imperial) Bundle Diameter Min. (Imperial) Bundle Diameter Min. (Metric) Bundle Diameter Max. (Imperial) Bundle Diameter Max. (Imperial) Nominal Diameter (Imperial) Nominal Diameter (Metric)

generated on: 4/28/2017

170-03142



Material and Specifications Flammability			_
Package Quantity (Imperial) Package Quantity (Metric) Customs Number(Schedule B) Package In Fig. 170°C to +125°C) Pes Ves UL Recognized (US) Yes 150ft Package Quantity (Metric) Customs Number(Schedule B) Weight (imperial) 2.1lbs		Flammability	VW-1
UL Recognized (US) UL Recognized (US and Canada) Yes Logistic and Packaging Package Quantity (Imperial) Package Quantity (Metric) Customs Number(Schedule B) Weight (imperial) 2.1lbs		Operating Temperature	-94°F to +248°F (-70°C to +125°C)
UL Recognized (US and Canada) Packaging Package Quantity (Imperial) Package Quantity (Metric) Package Quantity (Metric) Customs Number(Schedule B) Weight (imperial) 2.1lbs		ROHS Compliant	Yes
Logistic and Packaging Package Quantity (Imperial) Package Quantity (Metric) Package Quantity (Metric) Customs Number(Schedule B) Weight (imperial) 2.1lbs		UL Recognized (US)	Yes
Package Quantity (Imperial) Package Quantity (Metric) Package Quantity (Metric) Customs Number(Schedule B) Weight (imperial) 2.1lbs		UL Recognized (US and Canada)	Yes
Package Quantity (Metric) 45.72m Customs Number(Schedule B) 3926909987 Weight (imperial) 2.1lbs			
Customs Number(Schedule B) 3926909987 Weight (imperial) 2.1lbs		Package Quantity (Imperial)	150ft
Weight (imperial) 2.1lbs		Package Quantity (Metric)	45.72m
		Customs Number(Schedule B)	3926909987
Weight (Metric) 0.95kg		Weight (imperial)	2.1lbs
		Weight (Metric)	0.95kg

generated on: 4/28/2017