

111-12450



Article Number: 111-12450

Description: Heavy-Duty Cable Tie, 30" Long, 120lb Tensile Strength, PA66HS, Black, 50/pkg

Base Data	
Local Order Number	T120L0HSK2
Type	T120L
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"> <li>• Heat stabilized heavy-duty cable ties provide excellent resistance to high heat exposures.</li> <li>• Head design provides high tensile strength with very low insertion force.</li> <li>• Bent tail ensures a quick and simple installation.</li> </ul>
Quantity Per	bag
Product Description	HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Heavy-Duty Cable Tie, 30" Long, 120lb Tensile Strength, PA66HS, Black, 50/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	120.0lbs
Minimum Tensile Strength (Metric)	535.0N
Length L (Imperial)	30.0"
Length L (Metric)	760.0mm
Fixation Method	None
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.3"
Width W (Metric)	7.6mm
Bundle Diameter Min. (Imperial)	0.23"
Bundle Diameter Min. (Metric)	5.76mm

111-12450



Product Dimensions	Bundle Diameter Max. (Imperial)	8.85"
	Bundle Diameter Max. (Metric)	225.0mm
	Thickness T (Metric)	1.9mm
Material and Specifications		
	Material	Polyamide 6.6 heat stabilized (PA66HS)
	Material Shortcut	PA66HS
	Flammability	UL 94 V2
	Halogenfree	Yes
	Operating Temperature	-40°F to +257°F (-40°C to +125°C)
	ROHS Compliant	Yes
	Certification/Specification	VG U48/04103
	UL Listed (US and Canada)	Yes
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	50
	Package Quantity (Metric)	50
	Customs Number(Schedule B)	3926909987
	Weight (Metric)	2.48kg