

Article Number: 184-11012

Slotted Cable and Wiring Duct, High-Density, 1" x 1.5", Non-Adhesive, PVC, White, 120 ft/carton Description:

Base Data		
	Local Order Number	184-11012
		SLHD1X1.5
	Туре	
	Color	White (WH)
	Features and Benefits	 Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance. Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation. Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to accommodate compact designs and ease installation.
	Quantity Per	carton
	Product Description	Pro-Duct high density, slotted wiring duct features narrow fingers, a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.
	Technical Description	Non-Adhesive
	Short Description	Slotted Cable and Wiring Duct, High-Density, 1" x 1.5", Non-Adhesive, PVC, White, 120 ft/carton
Product Dimensions		
	Length L (Imperial)	6.0ft
	Length L (Metric)	1.83m
	Width W (Imperial)	1.0"
	Width W (Metric)	25.4mm
	Width W2 (Imperial)	1.0"
	Width W2 (Metric)	25.4mm
	Width W3 (Imperial)	0.16"
	Width W3 (Metric)	4.1mm
	Width W4 (imperial)	0.4"
	Width W4 (metric)	10.2mm
	Width W5 (imperial)	1.19"
	Width W5 (metric)	30.2mm

4/28/2017 generated on:

184-11012



Product Dimensions Height H (Imperial) 1.57" Height H (Metric) 39.9mm Mounting Hole Centers (Imperial) 2.0" Material and Specifications Material Polyvinylchloride (PVC) Material Shortcut PVC Flammability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification UL Logistic and Packaging Yes Logistic and Packaging Package Quantity (Imperial) 120ft			
Material and Specifications Material Specifications Material Polyvinylchloride (PVC) Material Shortcut PVC Flammability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification UL UL Recognized (US) Yes Logistic and Packaging Package Quantity (Imperial) 120ft		Height H (Imperial)	1.57"
Material and Specifications Material Polyvinylchloride (PVC) Material Shortcut PVC Flammability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification UL UL Recognized (US) Yes Logistic and Packaging Package Quantity (Imperial) 120ft		Height H (Metric)	39.9mm
Material Polyvinylchloride (PVC)		Mounting Hole Centers (Imperial)	2.0"
Material Shortcut PVC Flammability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification UL UL Recognized (US) Yes Logistic and Packaging Package Quantity (Imperial) 120ft			
Flammability Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification UL UL Recognized (US) Logistic and Packaging Package Quantity (Imperial) 120ft		Material	Polyvinylchloride (PVC)
Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification UL UL Recognized (US) Yes Logistic and Packaging Package Quantity (Imperial) 120ft		Material Shortcut	PVC
ROHS Compliant Certification/Specification UL UL Recognized (US) Logistic and Packaging Package Quantity (Imperial) 120ft		Flammability	self-extinguishing
Certification/Specification UL UL Recognized (US) Logistic and Packaging Package Quantity (Imperial) 120ft		Operating Temperature	+122°F (+50°C)
UL Recognized (US) Logistic and Packaging Package Quantity (Imperial) 120ft		ROHS Compliant	Yes
Logistic and Packaging Package Quantity (Imperial) 120ft		Certification/Specification	UL
Packaging Package Quantity (Imperial) 120ft		UL Recognized (US)	Yes
		Package Quantity (Imperial)	120ft
Package Quantity (Metric) 36.6m		Package Quantity (Metric)	36.6m
Customs Number(Schedule B) 3925900000		Customs Number(Schedule B)	3925900000

generated on: 4/28/2017