

Article Number: 596-00850

RATED MAX POWER-POINT CURRENT	
RATED MAX POWER-POINT VOLTAGE	
MAXIMUM SYSTEM VOLTAGE	
MAXIMUM CIRCUIT CURRENT	
MAX RATED OUTPUT CURRENT OF THE CHARGE CONTROLLER IF INSTALLED	

Description: Solar Label, Printable, DC Module, 4.0" x 2.0", PET, Red, 10/pkg

Base Data	
Local Order Number	596-00850
Type	DC201110
Color	Red (RD)
Features and benefits	<ul style="list-style-type: none"> • Made with UV-stable inks and materials for durability and weather resistance. • Polyester is resistant to chemicals and solvents and will remain legible in dirty environments. • High abrasion and scuff resistance for high-performance labeling. • Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
Quantity Per	reel
Product Description	HellermannTyton pre-printed Solar Rating labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
Technical Description	Printable Solar Label, DC Module Label, 4.0" X 2.0", Red
Local Order Number 2	Cross Reference = 50 per roll: 596-00253; Printable Metal Solar Placard 5 pack: 596-00839; Engravable Metal Solar Placard 5 pack: 596-00863; Spanish version 50 per roll: 596-00817
Short Description	Solar Label, Printable, DC Module, 4.0" x 2.0", PET, Red, 10/pkg
Product Dimensions	
Length L (Imperial)	2.0"
Length L (Metric)	50.8mm
Width W (Imperial)	4.0"
Width W (Metric)	101.6mm
Height H (Imperial)	2.0"
Height H (Metric)	50.8mm

596-00850



Material and Specifications		
	Material	Type 840/926, Polyester (PET), white (WH) UV stable w/ clear Polyester laminate
	Material Shortcut	840/926
	Adhesive	Acrylic
	Adhesive Operating Temperature	-40°F to +180°F (-40°C to +82°C)
	Halogenfree	Yes
	Operating Temperature	-40°F to +302°F (-40°C to +150°C)
	ROHS Compliant	Yes
	Certification/Specification	NEC2014
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	10
	Package Quantity (Metric)	10
	Customs Number(Schedule B)	3919905060