HellermannTyton



Article Number: 170-03190

Description: Braided Wrap, Aluminum Laminated Fiberglass, 4' Long Stick, .25" Dia, AL/GF, Silver, 50/box

Base Data		
	Local Order Number	170-03190
	Туре	BSHTTSW14SB
	Color	Silver (SR)
	Features and Benefits	 A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion. Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments. Cuts with ordinary scissors for fast, easy application.
	Quantity Per	box
	Product Description	Aluminum Laminated Fiberglass Wrap sleeving combines the protection of bonded aluminum and fiberglass into a robust solution that deflects radiant heat away from sensitive wires and cables. Wrap-around design allows for fast and easy installation and maintenance.
	Short Description	Braided Wrap, Aluminum Laminated Fiberglass, 4' Long Stick, .25" Dia, AL/GF, Silver, 50/box
Product Dimensions		
	Length L (Imperial)	4.0ft
	Length L (Metric)	1.22m
	Reel Length (imperial)	4.0ft
	Diameter D (imperial)	0.25"
	Diameter D (metric)	6.35mm
	Nominal Diameter (Imperial)	1/4"
	Nominal Diameter (Metric)	6.35mm
	Wall Thickness WT (Imperial)	.042"
	Wall Thickness WT (Metric)	1.06mm
Material and Specifications		
	Material	Glass fiber with aluminium foil (GF-AL)
	Material Shortcut	GF-AL

170-03190

HellermannTyton

Material and Specifications	Flammability	non flammable
	Operating Temperature	-76°F to +491°F (-60°C to +255°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	50
	Package Quantity (Metric)	50
	Customs Number(Schedule B)	7019901000