HellermannTyton

Article Number: 170-03098



Plenum Rated Expandable Braided Sleeving (Halar), .125" Dia, Black, 225 ft/reel

Base Data		
	Local Order Number	170-03098
	Туре	BSHLR180
	Color	Black (BK)
	Features and Benefits	 Meets UL 2024 and NFPA 262 specifications meets requirements for use in plenum applications. Technically advanced monofilament material is rated as low smoke, flame resistant and can withstand exposure to Cobal 60 radiation. Exceeds requirements of FMVSS 302 as well as aviation industry requirements of FAR25.
	Quantity Per	reel
	Product Description	Halar self-extinguishing sleeving is used where flammability, high temperature endurance and low outgassing are the primary concern.
	Short Description	Plenum Rated Expandable Braided Sleeving (Halar), .125" Dia, Black, 225 ft/reel
Product Dimensions		
	Length L (Imperial)	225.0ft
	Length L (Metric)	68.6m
	Reel Length (imperial)	225.0ft
	Bundle Diameter Min. (Imperial)	0.094"
	Bundle Diameter Min. (Metric)	2.4mm
	Bundle Diameter Max. (Imperial)	0.25"
	Bundle Diameter Max. (Metric)	6.4mm
	Nominal Diameter (Imperial)	1/8"
	Nominal Diameter (Metric)	3.1mm
Material and Specifications		
	Material	Polyamide 6.6 (PA66E/CTFE)
	Material Shortcut	PA66E/CTFE
	Flammability	UL VW-1

170-03098

HellermannTyton

Material and Specifications	Operating Temperature	-103°F to +302°F (-75°C to +150°C)
	ROHS Compliant	Yes
	Certification/Specification	UL2024
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	225ft
	Package Quantity (Metric)	68.58m
	Customs Number(Schedule B)	3926909987
	Weight (imperial)	0.6lbs
	Weight (Metric)	0.27kg