

16 dB Coupler 5 - 1225 MHz

Rev. V1

#### **Features**


- 16 dB Coupling Ratio
- Surface Mount
- · Available on Tape and Reel
- · Excellent Temperature Stability
- RoHS Compliant and lead free
- 260°C Reflow Compatible



The MACP-011036 is a 16 dB coupler in a low cost, surface mount package. Ideally suited for broadband CATV applications.



#### **Functional Schematic**



# **Ordering Information**

Part Number	Description	
MACP-011036	900 piece reel	
MACP-011036-TB	Sample Test Board	

# **Pin Configuration**

Pin No.	Function	
1	Input	
2	Ground	
3	Coupled	
4	Isolated	
5	Not Connected	
6	Output	



16 dB Coupler 5 - 1225 MHz

Rev. V1


# Electrical Specifications: Freq. = 5 - 1225 MHz, $T_A = 25$ °C, $Z_0 = 75 \Omega$ , $P_{in} = 0 \text{ dBm}$

Parameter	Conditions	Units	Min.	Тур.	Max.
Coupling Ratio	_	dB	_	16	_
Coupling (Pin 1- Pin 3)	5 - 1225 MHz	dB	16.7	16	15.7
Main Line Loss (Pin 1- Pin 6)	5 - 1000 MHz 1000 - 1225 MHz	dB	_	0.8 1.0	0.9 1.2
Isolation (Pin 1- Pin 4)	5 - 500 MHz 500 - 1225 MHz	dB	31 26	34 28	_
Input Return Loss (Pin 1)	5 - 500 MHz 500 - 1225 MHz	dB	20 16	22 18	_
Output Return Loss (Pin 6)	5 - 500 MHz 500 - 1225 MHz	dB	20 14	22 16	_
Coupling Return Loss (Pin 3)	5 - 500 MHz 500 - 1225 MHz	dB	20 14	22 16	_

# **Absolute Maximum Ratings**

Parameter	Absolute Maximum
Input Power	0.5 W
DC Current	500 mA
Operating Temperature	-40°C to +85°C


# **Application Schematic**








16 dB Coupler 5 - 1225 MHz Rev. V1


# Typical Performance Curves<sup>1</sup>















1. Full temperature plots available on request.




16 dB Coupler 5 - 1225 MHz Rev. V1

### **Outline Drawing**




### **PCB Layout**



- 1. Dimensions in mm.
- 2. Tolerance: ±0.2mm unless otherwise noted.
- 3. Model number and lot code printed on reel.
- 4. Plating finish: ENIG on both sides, 0.05 to 0.1 μm gold over 3 to 6 μm nickel

# **Carrier Tape Orientation**



# **Tape & Reel Information**

Parameter	Units	Value		
Qty per reel	-	900		
Reel Size	mm	330		
Tape Width	mm	16.00		
Pitch	mm	12.00		
Orientation	-	F45		

Reference Application Note ANI-019 for orientation

# MACP-011036



16 dB Coupler 5 - 1225 MHz

Rev. V1

#### M/A-COM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with M/A-COM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppels or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.