HellermannTyton



Article Number: 132-00011

Button Head Cable Tie, 15.0" Long, 4.3" Max Bundle Dia, 105lb, PA66HIRHSUV/PA66HS, Black, 50/pkg Description:

Base Data		
	Local Order Number	132-00011
	Туре	BT105L
	Color	Black (BK)
	Features and Benefits	 Unique two piece tie allows parallel entry and exit through the head for easy assembly. High impact, heat stabilized material gives strength needed for trucking and heavy equipment applications.
	Quantity Per	bag
	Product Description	The button head tie is a two piece tie providing for parallel entry and exit through the head. The strap contains serrations on both sides, and has two opposed pawls recessed within a domed head. This design allows the strap to be directed clockwise or counter-clockwise prior to insertion into the head, enabling bidirectional looping.
	Short Description	Button Head Cable Tie, 15.0" Long, 4.3" Max Bundle Dia, 105lb, PA66HIRHSUV/PA66HS, Black, 50/pkg
Product Dimensions		
	Minimum Tensile Strength (Imperial)	105.0lbs
	Minimum Tensile Strength (Metric)	467N
	Length L (Imperial)	15.0"
	Length L (Metric)	381.5mm
	Fixation Method	Connector Clip
	Identification Plate Position	none
	Releasable Closure	No
	Tie Closure	plastic pawl
	Variant	Outside Serrated
	Width W (Imperial)	0.22"
	Width W (Metric)	5.6mm
	Bundle Diameter Min. (Imperial)	0.06"
	Bundle Diameter Min. (Metric)	1.5mm

generated on: 4/28/2017

132-00011



Product Dimensions	Bundle Diameter Max. (Imperial)	4.3"
	Bundle Diameter Max. (Metric)	110.0mm
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
	Material Shortcut	PA66HS
	Material Cable Tie	Polyamide 6.6 high impact modified, heat and UV-resistant (PA66HIRHSUV)
	Flammability	UL 94 HB
	Material Head	Polyamide 6.6 heat stabilized (PA66HS)
	Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Logistic and Packaging		
	Package Quantity (Imperial)	50
	Package Quantity (Metric)	50
	Customs Number(Schedule B)	3926909987

generated on: 4/28/2017