

# Model #: P944-06I

# 6-inch Serial ATA (SATA) Power Cable (4Pin to 15pin)



# **Highlights**

- Connects SATA drive to internal power source
- Supports most current version of Serial ATA
- Meets the newly released updates and listed in Errata 029
- Supports a data transfer rate of 150-MBps

# **Description**

Tripp Lite expands its line of hard drive cables with the introduction of our new line of Serial ATA cables. The Serial ATA power cable connects any Serial ATA drive to any standard internal power connector. These new hard drives are perfect for the desktop or server that has multiple drives. This cable offers easy installation and comes with 15 pin/4 pin male connectors.

# System Requirements

- Serial ATA device
- Serial ATA controller

## Package Includes

• 6-in. Serial ATA (SATA) Power Adapter Cable 15Pin/4Pin

#### **Features**

- Connects any Serial ATA drive to a standard internal power connector
- Meets serial ATA 1.0 standards

# **Specifications**

OVERVIEW		
Intended Application	Connecting Peripherals, Powering Devices	
Cable Type	SATA	
INPUT		
Cable Length (in.)	6	
UPC Codes		
Unit Carton UPC#	037332117779	
PHYSICAL		

Color	Red			
Style	SATA			
CONNECTIONS				
Connector A	15 PIN SATA POWER			
Connector B	4 PIN (INTERNAL)			
Number of Connectors	2			
WARRANTY				
Product Warranty Period (Worldwide)	Lifetime limited warranty			

# **Related Items**

### **Optional Products**

Related Model	Description	Qty.
P940-19I	19-inch Serial ATA (SATA) Signal Cable (7Pin/7Pin)	1
P940-39I	39-inch Serial ATA (SATA) Signal Cable (7Pin/7Pin)	1
P942-19I	19-inch Serial ATA (SATA) Signal Cable (7Pin/7Pin-Down)	1
P944-06I	6-inch Serial ATA (SATA) Power Cable (4Pin to 15pin)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?variables.txtModelID=2648.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.