

596-00045

HellermannTyton

Article Number: 596-00045

Description: Thermal Transfer Labels, Self-Laminating, 1.5" x .70" x 1.437", 2 Across, VL, White, 2500/roll



Base Data	
Local Order Number	TAG53T2-100B
Type	TAG53T2
Color	White (WH)
Features and Benefits	<ul style="list-style-type: none"> • HellermannTyton Self-Laminating Labels come on rolls on a standard 3" core for easy loading into a printer or caddy. • Labels are conformable so that they can bend around small gauge wires and tight bends without coming loose over time. • Labels are UL recognized for indoor and outdoor use to expand application options. • HellermannTyton thermal transfer labels work in any thermal transfer printer so that the use always has options to get labels printed without being locked into a single vendor.
Quantity Per	reel
Product Description	HellermannTyton thermal transfer self-laminating labels are a conformable vinyl film with a white printable surface followed by a clear tail that laminates the printed text when applied to a wire or cable. The labels are UL recognized for indoor and outdoor use with an aggressive acrylic adhesive that allows the label to bond to large and small diameter wires.
Short Description	Thermal Transfer Labels, Self-Laminating, 1.5" x .70" x 1.437", 2 Across, VL, White, 2500/roll
Product Dimensions	
Length L (Imperial)	1.44"
Length L (Metric)	36.49mm
Width W (Imperial)	1.5"
Width W (Metric)	38.11mm
Height H (Imperial)	1.44"
Height H (Metric)	36.49mm
Height H2 (Imperial)	1.43"
Height H2 (Metric)	36.5mm
Height of printable area (imperial)	0.70"
Height of printable area (metric)	17.78mm
Bundle Diameter Max. (Imperial)	0.29"

596-00045

HellermannTyton

Product Dimensions	Horizontal Repeat HR (metric)	38.1mm
	Horizontal Repeat HR (imperial)	1.50"
	Print Method	Thermal transfer
	Thickness T (Metric)	25µm
	Vertical Repeat VR (imperial)	1.62"
	Vertical Repeat VR (metric)	41.28mm
	Width of Liner WL (imperial)	3.35"
	Width of Liner WL (metric)	89.05mm
Material and Specifications		
	Material	Type 100B, Vinyl (PVC), white transparent (WH/CL), self laminating
	Material Shortcut	100B
	Adhesive	Acrylic
	Adhesive Operating Temperature	-40°F to +194°F (-40°C to +90°C)
	Minimum Application Temperature	from +50°F (from +10°C)
	Operating Temperature	-40°F to +194°F (-40°C to +90°C)
	ROHS Compliant	Yes
Certification/Specification	UL-Recognized	
Logistic and Packaging		
	Package Quantity (Imperial)	2500
	Package Quantity (Metric)	2500
	Customs Number(Schedule B)	3919102055
	Labels per Row	2
	Weight (Metric)	0.56kg