

117-05501

Article Number: 117-05501



Description: Double-Head Cable Tie, 15.7" Long, 50lb Tensile Strength, PA66, Black, 50/pkg

Base Data	
Local Order Number	T120RDH0K2
Type	T120RDH
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"> • The tie contains a dual locking design to secure two bundles at once. • Head design can also provide spacing between parallel bundles. • Bent tail allows for quick insertion into head.
Quantity Per	bag
Product Description	The double head cable tie was designed with a dual locking head to secure two bundles simultaneously. The head also provides separation between bundles or bundles running parallel to each other. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Double-Head Cable Tie, 15.7" Long, 50lb Tensile Strength, PA66, Black, 50/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	120.0lbs
Minimum Tensile Strength (Metric)	535.0N
Length L (Imperial)	15.7"
Length L (Metric)	398.0mm
Bundle Diameter 2nd Loop Max. (Imperial)	2.0"
Fixation Method	None
Identification Plate Position	none
Releasable Closure	No
Variant	Inside Serrated
Width W (Imperial)	0.3"
Width W (Metric)	7.6mm
Bundle Diameter Min. (Imperial)	0.19"
Bundle Diameter Min. (Metric)	4.6mm
Bundle Diameter Max. (Imperial)	2.0"

117-05501



Product Dimensions	Bundle Diameter Max. (Metric)	101.6mm
	Bundle Diameter 1st Loop Max. (Imperial)	4.0"
Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	ROHS Compliant	Yes
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	50
	Package Quantity (Metric)	50
	Customs Number(Schedule B)	3926909987