## **HellermannTyton**



Article Number: 170-03107

Description: Plenum Rated Expandable Braided Sleeving (Halar), .75" Dia, WH, 75ft/reel

Base Data		
	Local Order Number	170-03107
	Туре	BSHLR3410
	Color	White (WH)
	Features and Benefits	<ul> <li>Meets UL 2024 and NFPA 262 specifications meets requirements for use in plenum applications.</li> <li>Technically advanced monofilament material is rated as low smoke, flame resistant and can withstand exposure to Cobal 60 radiation.</li> <li>Exceeds requirements of FMVSS 302 as well as aviation industry requirements of FAR25.</li> </ul>
	Quantity Per	reel
	Product Description	Halar self-extinguishing sleeving is used where flammability, high temperature endurance and low outgassing are the primary concern.
	Short Description	Plenum Rated Expandable Braided Sleeving (Halar), .75" Dia, WH, 75ft/reel
Product Dimensions		
	Length L (Imperial)	75.0ft
	Length L (Metric)	22.9m
	Reel Length (imperial)	75.0ft
	Bundle Diameter Min. (Imperial)	0.5"
	Bundle Diameter Min. (Metric)	12.7mm
	Bundle Diameter Max. (Imperial)	1.25"
	Bundle Diameter Max. (Metric)	31.8mm
	Nominal Diameter (Imperial)	3/4"
	Nominal Diameter (Metric)	19.1mm
Material and Specifications		
	Material	Polyamide 6.6 (PA66E/CTFE)
	Material Shortcut	PA66E/CTFE
	Flammability	UL VW-1

## 170-03107

## **HellermannTyton**

Material and Specifications	Operating Temperature	-103°F to +302°F (-75°C to +150°C)
	ROHS Compliant	Yes
	Certification/Specification	UL2024
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	75ft
	Package Quantity (Metric)	22.86m
	Customs Number(Schedule B)	3926909987
	Weight (imperial)	1.28lbs
	Weight (Metric)	0.58kg