

Article Number: 596-00189

Description: Plastic button base, with locators, 1.12" X 1.87", Plastic,

Black, 100/pkg

1	
Local Order Number	596-00189
Туре	PTSA-22
Color	Black (BK)
Features and benefits	<ul> <li>The legend bases can be fixed to flat surfaces by a rivet, cable ties, screws and also come with an adhesive backing for easy installation.</li> <li>Used with the legend inserts and clear covers, the bases provide durable and permanent identification.</li> </ul>
Quantity Per	pack
Product Description	Plastic Nameplate labels are less costly than plastic or metal engraved plates, saving material costs. Plastic Nameplate labels are made of a UL94VO rated polycarbonate that can be mounted mechanically or using an adhesive backing. HellermannTyton thermal transfer or laser labels can be printed and applied to the inserts and covered with a clear plastic cover to protect printed text.
Technical Description	Plastic button base, with locators, 1.12" X 1.87", Plastic, Black
Short Description	Plastic button base, with locators, 1.12" X 1.87", Plastic, Black, 100/pkg
Self adhesive (Yes/No)	Yes
Width W (Imperial)	1.12"
Width W (Metric)	28mm
Height H (Imperial)	1.87"
Height H (Metric)	47mm
Mounting Hole Diameter D (Imperial)	0.88"
Mounting Hole Diameter D (Metric)	22.35 mm
Horizontal Repeat HR (metric)	28mm
Horizontal Repeat HR (imperial)	1.12"
Print Method	Thermal transfer
Vertical Repeat VR (metric)	47mm
Vertical Repeat VR (imperial)	1.87"
	Type Color Features and benefits  Quantity Per Product Description  Technical Description  Short Description  Self adhesive (Yes/No)  Width W (Imperial)  Width W (Metric)  Height H (Imperial)  Height H (Metric)  Mounting Hole Diameter D (Imperial)  Mounting Hole Diameter D (Metric)  Horizontal Repeat HR (metric)  Horizontal Repeat HR (imperial)  Print Method  Vertical Repeat VR (metric)

generated on: 5/2/2017

## 596-00189



Material and Specifications		
	Material	Polycarbonate (PC)
	Material Shortcut	PC
	Adhesive	Acrylic
	Adhesive Operating Temperature	-22°F to +266°F (-30°C to +130°C)
	Flammability	UL 94 V0
	Operating Temperature	-22°F to +266°F (-30°C to +130°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	100
	Package Quantity (Metric)	100
	Customs Number(Schedule B)	3919905060

generated on: 5/2/2017