

113-05419

Article Number: 113-05419

Description: Screw-Mount Cable Tie, 15.4" Long, #10 Screw, 4.0" Max Bundle Dia, 50lb, PA66HS, Natural, 100/pkg



Base Data	Local Order Number	T50ML9C2
	Type	T50ML
	Color	Natural (NA)
	Features and Benefits	<ul style="list-style-type: none"> • Mount design secures firmly with any #10 Screw. • Screw mount style creates low insertion and high extraction force.
	Quantity Per	bag
	Product Description	Screw Mount Cable Ties are made of all plastic and provide a quick and simple method of mounting.
	Short Description	Screw-Mount Cable Tie, 15.4" Long, #10 Screw, 4.0" Max Bundle Dia, 50lb, PA66HS, Natural, 100/pkg
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		225N
Length L (Imperial)		15.4"
Length L (Metric)		390.0mm
Fixation Method		Fixing hole
Identification Plate Position		none
Releasable Closure		No
Tie Closure		plastic pawl
Variant		Inside Serrated
Width W (Imperial)		0.18"
Width W (Metric)		4.7mm
Height H (Imperial)		0.23"
Height H (Metric)		5.7mm
Bundle Diameter Min. (Imperial)		0.12"
Bundle Diameter Min. (Metric)		3.0mm
Bundle Diameter Max. (Imperial)	4.0"	

113-05419



Product Dimensions	Bundle Diameter Max. (Metric)	100.0mm
	Mounting Hole Diameter D (Imperial)	0.22"
	Mounting Hole Diameter D (Metric)	5.5 mm
	Thickness T (Imperial)	0.05"
	Cable Tie Head Length (Imperial)	0.79"
	Cable Tie Head Width (Imperial)	0.35"
	Thickness T (Metric)	1.2mm
Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +221°F (-40°C to +105°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
	Certification/Specification	UL ANSI/UL 1565
	UL Listed (US and Canada)	Yes
UL Recognized (US and Canada)	Yes	
Logistic and Packaging		
	Package Quantity (Imperial)	100
	Package Quantity (Metric)	100Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	2.9kg