
## **KEMET Part Number: PME271M660KR30**

(P276EL604K275A)



Film, Metallized Paper, Safety, PME271M/P276, 0.6 uF, 10%, 630 V, 275 V, 110C, Lead Spacing = 25.4mm



	I	,					
	Ш,		$\prod$			Lead:	Wire Leads
:    [] []				Approvals:	ENEC, UL, cUL		
					Construction:	Molded	
					Miscellaneous:	SRF= 1.6 MHz	
	'						
Dimensions		Specifications					
		30.5mm	n MAX			Capacitance:	0.6 uF
							4007

Dimensions		
L	30.5mm MAX	
Н	22mm MAX	
Т	15.3mm MAX	
S	25.4mm +/-0.5mm	
LL	30mm +5mm	
F	1mm NOM	

Packaging Specifications			
Packaging:	Bulk		
Packaging Quantity:	75		

Specifications			
Capacitance:	0.6 uF		
Capacitance Tolerance:	10%		
Voltage DC:	630 VDC		
Voltage AC:	275 VAC		
Temperature Range:	-40/+110C		
Rated Temperature:	110C		
Dissipation Factor:	1.3% 1kHz		
Insulation Resistance:	6.667 GOhms		
Max dVdt:	400 V		
Safety Class:	X2		

**General Information** 

Metallized Paper

PME271M/P276

Radial

Pulse

Yes

Dielectric:

Style:

RoHS:

Series: Features:

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

