

# Protect It! 6-Outlet Surge Protector, 4-ft. Cord, 540 Joules - Accommodates 2 Transformers

MODEL NUMBER: TLP64











### **Highlights**

- 6 outlets / 4 ft cord
- 540 joule rating
- \$20,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

### Package Includes

- TLP64
- Instruction manual with warranty information

#### Description

Tripp Lite's TLP64 offers economical AC surge suppression for protection of workstations, desktop PCs, point-of-sale terminals and other sensitive electronics. Built-in AC surge suppression shields connected equipment from damage and performance problems due to transient surges. TLP64 offers 6 total outlets, 4 foot cord and diagnostic LEDs to warn of suppressor damage. AC suppression rated at 540 joules shields equipment from surges and line noise. Attractive gray suppressor housing with keyhole mounting tabs offer convenient protection of desktop computer equipment and accessories. \$20,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

#### **Features**

- 6 outlets with integrated child safety covers
- 4ft cord
- Surge suppression rating: 540 joules
- EMI/RFI noise filtering
- Can accommodate up to 2 transformers without blocking remaining outlets
- Diagnostic LEDs indicate protection present and ground present
- . Keyhole supports for wall mounting
- Lighted power switch
- \$20,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)
- Automatic shutoff cuts power to outlets when the protection circuit has been compromised

## **Specifications**

ОИТРИТ	
Frequency Compatibility	60 Hz
Output Receptacles	(6) 5-15R





Output (Watts)	1800
Circuit Breaker (amps)	15
Overload Protection	15A resettable illuminated combo switch / circuit breaker
Transformer Accommodation	Supports 2 large transformer plug accessory without covering remaining outlets, accepts up to 4 transformers total
Outlet Safety Covers	6
Outlet Orientation	Block style 2 rows of 3 outlets
Right-Angle Outlets	No
INPUT	
Nominal Input Voltage(s) Supported	120V AC
Recommended Electrical Service	120V (110-125V)
Input Connection Type	NEMA 5-15P
Input Cord Length (ft.)	4
Input Cord Length (m)	1.22
Input Cord Gauge Type	14 gauge, SJT
Voltage Compatibility (VAC)	120
Maximum Surge Amps	36000
Right-Angle Plug	No
USER INTERFACE, ALERTS & COM	TROLS
Switches	
	Combination AC circuit breaker and 2 position red illuminated on/off power switch
Diagnostic LED Details	Combination AC circuit breaker and 2 position red illuminated on/off power switch  Built-in LED confirms suppressor "protection present" (green) status
Diagnostic LED Details  SURGE / NOISE SUPPRESSION	
SURGE / NOISE SUPPRESSION	Built-in LED confirms suppressor "protection present" (green) status
SURGE / NOISE SUPPRESSION  AC Suppression Joule Rating	Built-in LED confirms suppressor "protection present" (green) status  540
SURGE / NOISE SUPPRESSION  AC Suppression Joule Rating  AC Suppression Response Time	Built-in LED confirms suppressor "protection present" (green) status  540  < 1 ns
SURGE / NOISE SUPPRESSION  AC Suppression Joule Rating  AC Suppression Response Time  Protection Modes	Built-in LED confirms suppressor "protection present" (green) status  540  < 1 ns  Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
SURGE / NOISE SUPPRESSION  AC Suppression Joule Rating  AC Suppression Response Time  Protection Modes  Clamping Voltage (RMS)	Built-in LED confirms suppressor "protection present" (green) status  540  <1 ns  Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression  150
SURGE / NOISE SUPPRESSION  AC Suppression Joule Rating  AC Suppression Response Time  Protection Modes  Clamping Voltage (RMS)  UL1449 Let Through Rating	Built-in LED confirms suppressor "protection present" (green) status  540  <1 ns Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression  150  400v  Up to 40 dB
SURGE / NOISE SUPPRESSION  AC Suppression Joule Rating  AC Suppression Response Time  Protection Modes  Clamping Voltage (RMS)  UL1449 Let Through Rating  EMI / RFI Filtering	Built-in LED confirms suppressor "protection present" (green) status  540  <1 ns Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression  150  400v  Up to 40 dB
SURGE / NOISE SUPPRESSION  AC Suppression Joule Rating  AC Suppression Response Time  Protection Modes  Clamping Voltage (RMS)  UL1449 Let Through Rating  EMI / RFI Filtering  DATALINE SURGE SUPPRESSION	Built-in LED confirms suppressor "protection present" (green) status  540  < 1 ns  Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression  150  400v  Up to 40 dB



11.02 x 7.08 x 1.77
27.99 x 17.98 x 4.50
1.65
0.75
1.50 x 4.23 x 8.29
3.81 x 10.74 x 21.06
1.10
0.50
Plastic
Keyhole mounting tabs enable wall mounting
Light Gray
Light Gray
Light Gray
Distance between standard outlets = 28.5mm; Distance between standard outlet and transformer outlet = 48.5mm
119mm
UL1449 3rd Edition
UL1363
cUL
Exceeds IEEE 587 category A&B specifications
Lifetime limited warranty
\$20,000 Ultimate Lifetime Insurance

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies