HellermannTyton

Article Number: 596-00615

Description:

Solar Label, Reflective, CAUTION SOLAR CIRCUIT, 6.5" x 1.0", VL, Yellow, 50/roll

CAUTION: SOLAR CIRCUIT

Base Data		
	Local Order Number	596-00615
	Туре	CSCIRLBL
	Color	Yellow (YE)
	Features and benefits	 Made with UV stable inks and materials for durability and weather resistance Supplied with aggresive adhesive to ensure long life Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections Pre-printed labels offer significant time and cost savings over high priced engraved and lead time purchased markers
	Quantity Per	roll
	Product Description	HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
	Technical Description	Pre-Printed Reflective Solar Label, "CAUTION SOLAR CIRCUIT", 6.5" X 1.0", Yellow
	Local Order Number 2	Cross Reference = 10 per pack: 596-00673
	Short Description	Solar Label, Reflective, CAUTION SOLAR CIRCUIT, 6.5" x 1.0", VL, Yellow, 50/roll
Product Dimensions		
	Length L (Imperial)	6.5"
	Length L (Metric)	165.1mm
	Width W (Imperial)	6.5"
	Width W (Metric)	165.1mm
	Height H (Imperial)	1.0"
	Height H (Metric)	25.4mm
Material and Specifications		
	Material	Type 242/552, UV Stable Reflective Vinyl w/Acrylic Laminate

generated on: 4/29/2017

596-00615

HellermannTyton

Material and Specifications	Material Shortcut	242/552
	Adhesive	Acrylic
	Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
	Halogenfree	Yes
	Operating Temperature	-40°F to +174°F (-40°C to +79°C)
	ROHS Compliant	Yes
	Certification/Specification	UL969
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	50
	Package Quantity (Metric)	50
	Customs Number(Schedule B)	3919905060
	Labels per Column	1
	Labels per Row	1