

596-00006

# HellermannTyton

Article Number: 596-00006

Description: Thermal Transfer Labels, Self-Laminating, 1.0" x .5" x 1.43", 2 Across, VL, White, 5000/roll



Base Data	
Local Order Number	TAG22T2-100B
Type	TAG22T2
Color	White (WH)
Features and Benefits	<ul style="list-style-type: none"> <li>• Clear laminate provides excellent abrasion protection and chemical resistance.</li> <li>• Flexible material bends around small gauge wires and tight bends.</li> <li>• Labels are UL recognized and include a strong acrylic adhesive for indoor and outdoor use.</li> <li>• Standard 3" core can be used with HellermannTyton thermal transfer printers or most standard brands.</li> </ul>
Quantity Per	reel
Product Description	HellermannTyton self-laminating thermal transfer printer labels are a made of a flexible vinyl film with a white printable surface that easily conforms to wires. These labels include a clear "tail" that laminates printed text when applied. Labels are UL recognized for indoor and outdoor use and feature a strong acrylic adhesive designed to bond to both large and small diameter wires.
Short Description	Thermal Transfer Labels, Self-Laminating, 1.0" x .5" x 1.43", 2 Across, VL, White, 5000/roll
Product Dimensions	
Length L (Imperial)	1.43"
Length L (Metric)	36.3mm
Width W (Imperial)	1.0"
Width W (Metric)	25.4mm
Height H (Imperial)	1.43"
Height H (Metric)	36.3mm
Height H2 (Imperial)	1.43"
Height H2 (Metric)	36.3mm
Height of printable area (imperial)	0.5"
Height of printable area (metric)	12.7mm
Bundle Diameter Min. (Imperial)	0.137"
Bundle Diameter Min. (Metric)	3.5mm

596-00006



Product Dimensions	Bundle Diameter Max. (Imperial)	0.29"
	Bundle Diameter Max. (Metric)	7.6mm
	Horizontal Repeat HR (metric)	27.3mm
	Horizontal Repeat HR (imperial)	1.075"
	Print Method	Thermal transfer
	Thickness T (Metric)	75µm
	Vertical Repeat VR (imperial)	1.62"
	Vertical Repeat VR (metric)	41.28mm
	Width of Liner WL (imperial)	2.25"
	Width of Liner WL (metric)	57.1mm
Material and Specifications		
	Material	Type 100B, Vinyl (PVC), white transparent (WH/CL), self laminating
	Material Shortcut	100B
	Adhesive	Acrylic
	Adhesive Operating Temperature	-40°F to +194°F (-40°C to +90°C)
	Minimum Application Temperature	from +50°F (from +10°C)
	Operating Temperature	-40°F to +194°F (-40°C to +90°C)
	ROHS Compliant	Yes
Certification/Specification	UL-Recognized	
Logistic and Packaging		
	Package Quantity (Imperial)	5000
	Package Quantity (Metric)	5000
	Customs Number(Schedule B)	3919102055
	Labels per Column	2
	Labels per Row	2