

553-50209

HellermannTyton

Article Number: 553-50209

Description: Heat Shrink Labels, 1.5" (38.1mm), Single Sided, Unslit, PO-X, White 150/box



Base Data	
Local Order Number	553-50209
Type	HST39-13WH
Color	White (WH)
Features and Benefits	<ul style="list-style-type: none"> • Slide Slit and optional center slits for easy wire insertion. • Smooth surface for clean and legible printing. • Supplied on a ladder style carrier so that markers can be kitted after printing. • A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.
Quantity Per	box
Product Description	HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production.
Short Description	Heat Shrink Labels, 1.5" (38.1mm), Single Sided, Unslit, PO-X, White 150/box
Product Dimensions	
Length L (Imperial)	1.90"
Length L (Metric)	48.3mm
Printable (Yes/No)	Yes
Variant	Thin-Wall
Width W (Imperial)	1.90"
Width W (Metric)	48mm
Height H (Imperial)	2.26"
Height H (Metric)	57.4mm
Diameter Min. (Imperial)	0.51"
Diameter Max. (Imperial)	1.5"
Outside Diameter Max. (Imperial)	1.5"
Outside Diameter Max. (Metric)	38.1mm
Wall Thickness WT (Imperial)	0.04"

553-50209



Product Dimensions	Wall Thickness WT (Metric)	1.01mm
	Flexibility	Flexible
	Print Method	Thermal transfer
	Recovered Diameter d (metric)	13mm
	Recovered Diameter d (imperial)	0.51"
	Supplied Diameter D (imperial)	1.5"
	Supplied Diameter D (metric)	38.1mm
	Thickness T (Metric)	3.0µm
	Width of Liner WL (imperial)	3.0"
	Width of Liner WL (metric)	76.2mm
	Width of Printable Area (imperial)	1.9"
	Width of printable area (metric)	48.26mm
Material and Specifications		
	Material	Polyolefin, cross-linked (PO-X)
	Material Shortcut	PO-X
	Dielectric Strength (Metric)	19.7 kV min.
	Flammability	UL 224 VW-1
	Shrink Temperature	+194 °F (+90 °C)
	Operating Temperature	-67°F to +275°F (-55°C to +135°C)
	ROHS Compliant	Yes
Certification/Specification	UL224 125 °C 600V VW-1	
Logistic and Packaging		
	Package Quantity (Imperial)	150
	Package Quantity (Metric)	150
	Customs Number(Schedule B)	3926909987
	Markers per row	1
	Weight (imperial)	1.48lbs
	Weight (Metric)	0.68kg