HellermannTyton

Article Number: 598-00273



Description: Handi-Pak Marker Booklet, 45 of 0–9 and 15 of L1–L3, T1–T3, White, 1/pkg

Base Data		
	Local Order Number	TCWM14
	Туре	TCWM14
	Color	White (WH)
	Features and Benefits	 Handi-Paks booklets fit in a pocket for easy transport and access. A single marker can be removed at the top of each label so that the terminal block can be marked and the remaining label can be used to mark the associated wire connected to the terminal. Markers are kitted on each page so that any marker can be removed without affecting the other markers on the page. Markers have a micro-perforation in the middle of each marker so that they can be broken into two pieces for use on small gauge wires, eliminating waste and reducing costs.
	Quantity Per	book
	Product Description	Handi-Paks are convenient pocket sized books that contain pages of black, pre- printed legends on a white background. The legends are printed on a plastic coated cloth label that remains flexible for use in identifying wires and cables. A strong adhesive assures long lasting identification on small wires, cables or anything requiring permanent or temporary identification.
	Technical Description	Handi-Pak, 45 of 0–9 and 15 of L1–L3, T1–T3, White
	Short Description	Handi-Pak Marker Booklet, 45 of 0–9 and 15 of L1–L3, T1–T3, White, 1/pkg
Product Dimensions		
	Length L (Imperial)	1.625"
	Length L (Metric)	41.27mm
	Width W (Imperial)	0.25"
	Width W (Metric)	6.35mm
	Height H (Imperial)	1.625"
	Height H (Metric)	41.27mm
	Outside Diameter Min. (Imperial)	0.1"
	Outside Diameter Min. (Metric)	2.54mm
	Outside Diameter Max. (Imperial)	0.375"
	Outside Diameter Max. (Metric)	9.52mm

598-00273

HellermannTyton

Material and Specifications Material Vinyl Cloth (TYHC) Material Shortcut Vinyl Cloth (TYHC) Material Shortcut TYHC Adhesive Rubber Adhesive Operating Temperature -40°F to +248°F (-40°C to +120°C) Minimum Application Temperature from +50°F (from +10°C)	
Material ShortcutTYHCAdhesiveRubberAdhesive Operating Temperature-40°F to +248°F (-40°C to +120°C)Minimum Application Temperaturefrom +50°F (from +10°C)	
AdhesiveRubberAdhesive Operating Temperature-40°F to +248°F (-40°C to +120°C)Minimum Application Temperaturefrom +50°F (from +10°C)	
Adhesive Operating Temperature-40°F to +248°F (-40°C to +120°C)Minimum Application Temperaturefrom +50°F (from +10°C)	
Minimum Application Temperature from +50°F (from +10°C)	
Operating Temperature -40°F to +248°F (-40°C to +120°C)	
ROHS Compliant Yes	
Logistic and Packaging	
Package Quantity (Imperial) 1	
Package Quantity (Metric) 1	
Customs Number(Schedule B) 3919905060	
Labels per Column 3	
Labels per Row 15	
Labels per Sheet 45	