HellermannTyton



Article Number: 170-03141

Braided Sleeving, Split Wrap, Flame Retardant, .25" Dia, Black, 200 ft/bulk reel Description:

Local Order Number	170-03141
Туре	BSSWFR140B
Color	Black (BK)
Features and Benefits	 Split wrap design installs quickly, saving assembly time and future accessibility without disassembly. Unique construction retains shape and rigidity throughout unrolling. Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.
Quantity Per	box
Product Description	A lateral split, semi-rigid and flame retardant braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.
Short Description	Braided Sleeving, Split Wrap, Flame Retardant, .25" Dia, Black, 200 ft/bulk reel
Length L (Imperial)	200.0ft
Length L (Metric)	61.0m
Reel Length (imperial)	200.0ft
Bundle Diameter Max. (Imperial)	0.25"
Bundle Diameter Max. (Metric)	6.4mm
Nominal Diameter (Imperial)	1/4"
Nominal Diameter (Metric)	6.4mm
Material	Polyester (PET)
Material Shortcut	PET
Flammability	FAR 25
Operating Temperature	-94°F to +248°F (-70°C to +125°C)
	Type Color Features and Benefits Quantity Per Product Description Short Description Length L (Imperial) Length L (Metric) Reel Length (imperial) Bundle Diameter Max. (Imperial) Bundle Diameter Max. (Metric) Nominal Diameter (Imperial) Nominal Diameter (Metric) Material Material Shortcut Flammability

generated on: 4/28/2017

170-03141



Material and Specifications	ROHS Compliant	Yes
	UL Recognized (US and Canada)	Yes
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	200ft
	Package Quantity (Metric)	60.96m
	Customs Number(Schedule B)	3926909987
	Weight (imperial)	1.2lbs
	Weight (Metric)	0.54kg

generated on: 4/28/2017