## **HellermannTyton**



Article Number: 109-00115

Description: Q Tie, 20.5" Long, 120lb Tensile Strength, PA66HS, Black, 100/pkg

Base Data		
	Local Order Number	109-00115
	Туре	Q120M
	Color	Black (BK)
	Features and Benefits	<ul> <li>Open-head design with easily detectable slot opening allows for swift and easy insertion</li> <li>Pre-lock feature allows for a temporary hold</li> <li>The large ribbed tail permits an ergonomic installation</li> <li>Two rails on the strap ensure guidance through the cable tie head</li> </ul>
	Quantity Per	bag
	Product Description	Q Ties have a distinctive open-style head, a pre-lock function, and a large ribbed tail. The easily detectable slot opening offered with the tail and tie head offers ease of placement especially when working with gloves is necessary or for blind applications with limited view of the installation. The pre-lock feature allows for temporary holding of cable and wire bundles, permitting additional cables and wires to be placed without destroying the cable tie. Q Ties can be tensioned by hand or with one of HellermannTyton's mechanical cable tie application tools.
	Short Description	Q Tie, 20.5" Long, 120lb Tensile Strength, PA66HS, Black, 100/pkg
Product Dimensions		
	Minimum Tensile Strength (Imperial)	120.0lbs
	Minimum Tensile Strength (Metric)	530N
	Length L (Imperial)	20.5"
	Length L (Metric)	520mm
	Fixation Method	None
	Identification Plate Position	none
	Releasable Closure	No
	Tie Closure	plastic pawl
	Variant	Inside Serrated
	Width W (Imperial)	0.3"
	Width W (Metric)	7.7mm
	Bundle Diameter Min. (Imperial)	0.12"

## 109-00115

## **HellermannTyton**

Product Dimensions	Bundle Diameter Min. (Metric)	6.0mm
	Bundle Diameter Max. (Imperial)	5.1"
	Bundle Diameter Max. (Metric)	130mm
	Thickness T (Imperial)	0.07"
	Thickness T (Metric)	1.8mm
Material and Specifications		
	Material	Polyamide 6.6 heat stabilized (PA66HS)
	Material Shortcut	PA66HS
	Flammability	UL 94 V2
	Halogenfree	Yes
	Operating Temperature	-40°F to +221°F (-40°C to +105°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
	Certification/Specification	UL   ANSI/UL 746B
Logistic and Packaging		
	Package Quantity (Imperial)	100
	Package Quantity (Metric)	100Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces