

151-00663

HellermannTyton

Article Number: 151-00663

Description: Bundling Clip, Hole Diameter 6.2–6.8mm, Panel .7–5.7mm, PA66HIRHSUV, Black, 2000/box



Base Data	
Local Order Number	151-00663
Type	TC6FT6
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"> • Staggered fir tree branch design provides low insertion forces and high extraction forces for easy assembly. • Initial fir tree serves as a locating feature for assistance in blind assembly applications.
Quantity Per	box
Product Description	HellermannTyton's Bundling Clip includes an extended fir tree mount to allow for a wide panel thickness range (0.7 - 18.0 mm). Anti-sliding bars on the ends of the connection bar assist in preventing the cable ties or tape from sliding off the clip in high movement/vibration applications.
Short Description	Bundling Clip, Hole Diameter 6.2–6.8mm, Panel .7–5.7mm, PA66HIRHSUV, Black, 2000/box
Product Dimensions	
Length L (Imperial)	1.5"
Length L (Metric)	38.1mm
Fixation Method	Fir Tree
Width W (Imperial)	0.5"
Width W (Metric)	12.0mm
Height H (Imperial)	0.5"
Height H (Metric)	14.0mm
Height H2 (Imperial)	0.4"
Height H2 (Metric)	10.5mm
Panel Thickness Max. (Imperial)	0.71"
Panel Thickness Max. (Metric)	5.75mm
Panel Thickness Min. (Imperial)	0.03"
Panel Thickness Min. (Metric)	0.70mm
Mounting Hole Diameter D (Imperial)	0.26"

151-00663

HellermannTyton

Product Dimensions	Mounting Hole Diameter D (Metric)	6.1 - 6.9 mm
	Mounting Hole Diameter D Min. (Imperial)	0.24"
	Mounting Hole Diameter D Max. (Imperial)	0.27"
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
	Material Shortcut	PA66HIRHSUV
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +230°F (-40°C to +110°C)
Logistic and Packaging		
	Package Quantity (Imperial)	2000
	Package Quantity (Metric)	2000
	Customs Number(Schedule B)	3926909987