

112-12060



Article Number: 112-12060

Description: Heavy-Duty Cable Tie, 15.2" Long, 120lb Tensile Strength, PA66, Black, 50/pkg

Base Data	
Local Order Number	T120R0K2
Type	T120R
Color	Black (BK)
Features and benefits	<ul style="list-style-type: none"> • Heavy-duty design to offer higher tensile strength. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
Quantity Per	bag
Product Description	HellermannTyton heavy-duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Heavy-Duty Cable Tie, 15.2" Long, 120lb Tensile Strength, PA66, Black, 50/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	120.0lbs
Minimum Tensile Strength (Metric)	535.0N
Length L (Imperial)	15.2"
Length L (Metric)	387.0mm
Fixation Method	None
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.3"
Width W (Metric)	7.6mm
Bundle Diameter Min. (Imperial)	0.2"
Bundle Diameter Min. (Metric)	5.0mm
Bundle Diameter Max. (Imperial)	4.1"

112-12060



Product Dimensions	Bundle Diameter Max. (Metric)	105.0mm
Material and Specifications	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Flammability	UL 94 V2
	Halogenfree	Yes
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	ROHS Compliant	Yes
	Certification/Specification	MIL 53421
	UL Listed (US and Canada)	Yes
	UL Recognized (US and Canada)	Yes
	Logistic and Packaging	Package Quantity (Imperial)
Package Quantity (Metric)		50
Customs Number(Schedule B)		3926909987
Weight (Metric)		5.14kg