

595-23100

HellermannTyton

Article Number: 595-23100

Description: Dot Matrix Label, Self-Laminating, 1.0" x 1.5" x 7.437", 8 Across, White, 2500/pkg



Base Data	
Local Order Number	TAG23-100
Type	TAG23
Color	White (WH)
Features and Benefits	<ul style="list-style-type: none"> • Tabtag Dot Matrix labels are specifically made for use in dot matrix printers for fast and easy printing. • Labels come with a pin-feed margin to ensure that they can easily be loaded into any dot matrix printing system.
Quantity Per	pack
Product Description	Used with dot matrix printers, HellermannTyton TabTags can be used for virtually any labeling application. Unless noted, TabTags are mounted on pinfed, fan-folded sheets for use with computers, word processors, or typewriters. Manufactured in a wide range of standard sizes and materials, the dot matrix printable TabTags can meet a wide variety of labeling requirements.
Short Description	Dot Matrix Label, Self-Laminating, 1.0" x 1.5" x 7.437", 8 Across, White, 2500/pkg
Product Dimensions	
Length L (Imperial)	7.437"
Length L (Metric)	188.9mm
Self adhesive (Yes/No)	Yes
Variant	Adhesive label
Width W (Imperial)	1.0"
Width W (Metric)	25.4mm
Height H (Imperial)	1.5"
Height H (Metric)	38.1mm
Height H2 (Imperial)	7.437"
Height H2 (Metric)	188.9mm
Height of printable area (metric)	38.10mm
Bundle Diameter Min. (Imperial)	0.93"
Bundle Diameter Min. (Metric)	23.70mm

595-23100



Product Dimensions	Bundle Diameter Max. (Imperial)	1.87"
	Bundle Diameter Max. (Metric)	47.50mm
	Outside Diameter Min. (Imperial)	0.93"
	Outside Diameter Min. (Metric)	23.7mm
	Outside Diameter Max. (Imperial)	1.87"
	Outside Diameter Max. (Metric)	47.50mm
	Horizontal Repeat HR (metric)	27.94mm
	Horizontal Repeat HR (imperial)	1.100"
	Print Method	Dot-Matrix
	Thickness T (Metric)	75.0µm
	Vertical Repeat VR (imperial)	7.5"
	Vertical Repeat VR (metric)	190.50mm
	Width of Liner WL (imperial)	9.5"
	Width of Liner WL (metric)	241.30mm
Material and Specifications		
	Material	Type 100, Vinyl (PVC), white (WH), self laminating
	Material Shortcut	100
	Adhesive	Acrylic
	Adhesive Operating Temperature	-51°F to +200°F (-46°C to +93°C)
	Minimum Application Temperature	from +50°F (from +10°C)
	Operating Temperature	-51°F to +200°F (-46°C to +93°C)
	ROHS Compliant	Yes
Certification/Specification	UL-Recognized	
Logistic and Packaging		
	Package Quantity (Imperial)	2500
	Package Quantity (Metric)	2500
	Customs Number(Schedule B)	3919905060
	Labels per Column	8
	Labels per Row	8
	Weight (Metric)	0.08kg